



Parts & Accessories



Heating System and Outdoor Furnace Products

WoodMaster.com

Table of Contents

HEATING SYSTEM PRODUCTS

Heat Exchangers - Water-to-Air.....	1-5
Heat Exchangers - Water-to-Water.....	6-8
Heat Exchangers - Convection.....	9
Piping - ThermoPEX.....	10
Piping - EZ Lay and 1-1/4" PEX Crimp Fittings.....	11
Piping - Fittings.....	13
Circulators.....	14-15
Circulators & Related.....	16
Manifolds.....	18
HeatLink Products.....	19
Fittings and Tools - PEX.....	20-21
Fittings - Threaded.....	22-24
Fittings - Sharkbite.....	25
Fittings - Copper/Sweat.....	27
Fittings - Kits.....	28
Valves.....	34-36

OUTDOOR FURNACE PRODUCTS

Chimney.....	37-38
Corrosion Inhibitor, Treatment.....	39
Furnace Replacement Parts.....	40-41
AFS Replacement Parts.....	42
Flex Fuel Replacement Parts.....	43
Renovator Replacement Parts.....	44
Options and Tools.....	45
CleanFire Furnace Parts & Accessories.....	46-47
Maxim Furnace Parts & Accessories.....	48-49

24V Fan Conversion Kit	45	Chimney Tee Kits, Stainless Steel	47
Actuator, Thermal.	18	Cinch Tool	21
Adapter, 1" Crimp x 1" FPT	22	Clamp Crimp Ring, PEX Stainless Steel	20
Adapter, Brass	22	Clamp Crimp Ring Removal Tool	21
Adapter, Brass PEX 90° Elbow - Threaded Pipe.	20	Clamp, Hose, 1" or 1-1/4" (SDR-11)	13
Adapter, Brass PEX - Threaded Pipe	20	Clamp, Snaplock Chimney - 8".	37
Adapter, Female 1" NPT - for Manifold Kits	18	Cleaning Rod - CleanFire	47
Adapter, Female, 3/4" Hose, Brass	22	Cleaning Rod - Maxim	48
Adapter, Female - Copper Pipe	20	Cleaning Tool, Afterburner	47
Adapter, Male, 3/4" Hose, Brass	22	Cleaning Tool, Heat Exchanger	47
Adapter, PEX 90° Swoop Elbow	20	Connectors, Lever Nut.	49
Adapters, Female - Copper	27	Cord, Power Supply	17
Adapters, Male - Copper	27	Coupler, Brass	22
Adapters, PEX 90° Elbow	20	Coupling, 25mm PEX	13
Adapters, PEX - Copper Pipe	20	Couplings, 1/2" and 1" PEX.	13
Adapters, PEX - Threaded Pipe	20	Couplings, Copper	27
AFS Replacement Parts - Augers	42	Crimp Fittings Adapter Kit, 25mm to 1".	28
AFS Replacement Parts - Fire Pot	42	Crimp Fittings Kits with Single Pump and Heat Exchanger - CleanFire Models	30
AFS Replacement Parts - Motor Items	42	Crimp Fittings Kits with Single Pump and Heat Exchanger - Maxim M255 PE Models.	32
Air Handler Cabinet	3	Crimp Fittings Kits with Single Pump and Heat Exchanger - Traditional Models	31
Aquastat, Immersible - Adjustable	33	Crimp Kit, Brazed Plate to Boiler	28
Aquastats & Thermostats	33	Crimp Kit, Brazed Plate to Domestic Water	28
Ash Removal Systems	41	Crimp Kit, Fill Valve and Inline Strainer	28
Ash Scoop - Maxim.	48	Crimp Kit, Forced Air Heat Exchanger	28
Ash Shovel, Reaction Chamber	45	Crimp Tool, Universal	21
Auger Chains	41	CS-25 Alkalinity Builder	39
Auxiliary Auger Kits - Maxim	48	DISCAL® Air Separator	35
Auxiliary Auger Vibrator w/Timer Kit - Maxim	49	Dixell Temp Control	40
Bag Holder Kit - Maxim	49	Door Seal	46
Ball Valve	35	Door Seal, Silicone-Coated, 100-ft	46
Ball Valve, PEX	35	Draft Inducer Kits	38
Ball Valve, Sweat	35	Elbow, 45° Street	23
Blower & Motor	3	Elbow, 90° - Copper	27
Brush, Cleaning	27	Elbow, 90° - FPT	23
Brush, Stainless Steel	45	Elbow, 90° Reducing - Copper.	27
Bushing, Hex - NPT.	23	Elbow, 90° Street	23
Caleffi 2-Way Zone Valve, 1" Sweat	34	Elbow, 90° Street - Copper	27
Caleffi 2-Way Zone Valve, 3/4" FNPT	34	Elbow, Brass	22
Caleffi 3-Way Thermostatic Mixing Valve, 3/4" NPT.	35	Elbow, Vent - Copper	27
Caleffi 3-Way Zone Valve, FNPT	34	ETC Assembly, Wood Stove.	40
Caleffi 3-Way Zone Valve, Sweat	35	EZ Lay Insulated Pipe	11
Caleffi TankMixer, 3/4" NPT.	35	Fan Center Relay	33
Caleffi Zone Valve Switches	35	Fan Coil Unit, 50k Btu	2
Cap, Copper End	27	Fan Coil Unit, 100k Btu	2
Cap - for Manifold Kits	18	Fan Coil Unit, 220k Btu	2
Caps, Round Pipe	23	Fan Convactor (26k Btu).	1
Central PEX 1/2" Pipe	19	Fan Convactor, Corner (7k Btu)	1
Central PEX 1" Pipe.	13	Fan Convactor, Wall Mount (7k Btu)	1
Central PEX 1" Pipe Sections	13	Filter & Fill Valve Kits	8
Check Valves	34	Firebox Door	40
Check Valve, Swing - Brass	34	FireStar XP Outdoor Wi-Fi Module Kit	48
Chimney Attachment Ring	46	Fittings, 1-1/4" PEX (CTS)	11
Chimney Band Clamp Kit, 6".	38, 46	Fittings, Brass - for 1-1/4" PEX Pipe (SDR-11)	13
Chimney Band Clamp Kit, 8".	37, 36	Fittings Kit, Domestic Hot Water Plate Exchanger	28
Chimney Base Brace Kit, 6".	37	Fittings Kit, Forced Air Furnace Heat Exchanger.	29
Chimney Base Brace Kit, 8".	37	Fittings Kit, Push-fit - for Water-to-Water Heat Exchanger	7
Chimney Cap/Spark Arrestor	37, 46	Fittings Kit, Single Pump Crimp	29
Chimney Cleaning Kit - 6"	45	Fittings Kit, Single Pump Sharkbite®	29
Chimney Cleaning Kit - 8"	45	Fittings Kit, Water Heater - for Water-to-Water Heat Exchanger	7
Chimney Coupler.	37	Fittings, PEX	13
Chimney Guy-Wire Band, 6".	38, 47	Flange, 3/4" Isolation - with Drain Valve.	17
Chimney Guy-Wire Band Kit, 8".	37, 47	Flange Kit, Isolation	16
Chimney Rope Ring	47	Flanges, Pump.	16
Chimney Sections, 6" - CleanFire 300 and 500.	46	Flex Fuel Replacement Parts - Control Panel Displays	43
Chimney Sections, 6" - Maxim	38	Flex Fuel Replacement Parts - Grates	43
Chimney Sections, 8" - CleanFire 700/900	46	Flex Fuel Replacement Parts - Handles	43
Chimneys - Traditional Models	37	Flex Fuel Replacement Parts - Heat Exchanger Gaskets	43
Chimney Tee Covers	47		

Alphabetical Index

Flex Fuel Replacement Parts - I/O Board	43	Push-fit Fittings - Coupling, Straight	26
Flue Brush & Handle	48	Push-fit Fittings, Elbow	26
Gauges, Temperature	24	Push-fit Fitting, Tee	26
Gauge, Temperature - for Manifold Kits	18	Push-fit Fitting - Temperature Gauge	26
Grounding Rod Kit	47	Radiant Baseboard Heaters, Complete	9
Grundfos UPMS 20-58 F Circulator	14	Radiant Mixing Valve, Sweat	34
Grundfos UPMS 20-78 F Circulator	14	Ratchet Cinch Tool	21
Heat Exchanger Coil (50k Btu)	5	Reducer Bushing, Black	23
Heat Exchanger Coil (80k Btu)	5	Reducer Bushing, Brass	22
Heat Exchanger Coil (95k Btu)	5	Reducer, Copper	27
Heat Exchanger Coil (100k Btu)	4	Relay, 24-Volt	33
Heat Exchanger Coil (100k Btu)	5	Renovator Replacement Electronics	44
Heat Exchanger Coil (125k Btu)	5	Renovator Replacement Parts - Air Box Gasket Rope Kit	44
Heat Exchanger Coil (140k Btu)	5	Renovator Replacement Parts - Burn Pot	44
Heat Exchanger Coil (185k Btu)	5	Renovator Replacement Parts - Combustion Fan	44
Heat Exchanger Coil (220k Btu)	5	Replacement Door Rope	40
Heat Exchanger Coils	4	Replacement Fan	40
Heat Exchanger, Plate	6	Replacement Fan Cover	40
Heat Exchanger, Stainless 316L - for Swimming Pool	7	Replacement Harnesses	40
Heat Exchanger, Titanium Grade 1 - for Swimming Pool	8	Replacement Night Light Glass Cover	40
Hoe, Ash	45	Replacement On/Off Switch	41
Hoe, Firebox	45	Replacement Seal Kits and Gaskets	16
Hopper, 48-Bushel Kit w/Auger - Maxim M255 PE	48	Replacement Silicone	40
Hopper Vibrator Kit - Maxim	49	Replacement Stove Light w/Glass Cover	40
Hose Bibs, Brass	35	Replacement Temperature Probe	41
Kickspace Heaters	9	Replacement Thermistor	41
Manifold Kit Connectors	18	Replacement Thermowell	41
Manifold Kits	18	Replacement Vent Cap	41
Mixing Valve, 4-way FNPT	19	Replacement Water Level Light	40
MolyArmor 350 Corrosion Inhibitor	39	Replacement Water Pressure Switch	41
Moly/pH Single Strip Test Kit	39	Rope, Door Seal	46
Mounting Bracket, Plate Heat Exchanger	6	Scraper Tool	47
Mounting Brackets - Swimming Pool Heat Exchangers	8	Sediment Trapper Filter, Hot Water, 3/4"	45
Mounting Kit, Plate Heat Exchanger	6	Sharkbite Ball Valve	25
Mounting Kit, Plate Heat Exchanger, 5x12, Universal	6	Sharkbite Fitting - Adapter, Male	25
Mount Kit, Wall - Pump	17	Sharkbite Fitting - Coupling, Reducing	25
Multimeter, Digital Pocket	45	Sharkbite Fitting - Female Adapter	25
Nipple, Black	23	Sharkbite Fittings - Coupling, Straight	25
Nipple, Brass	22	Sharkbite Fittings, Elbow	25
Nipple, Brass Close	23	Sharkbite Fittings Kits with 30-Plate Heat Exchanger	32
Nipple, Close - Black	23	Sharkbite Fittings Kits with Single Pump and Heat Exchanger - CleanFire Models	29
Over Fire Air Tube	41	Sharkbite Fittings Kits with Single Pump and Heat Exchanger - Maxim M255 PE Models	31
PEX 1-1/4" Pipe (SDR-11)	13	Sharkbite Fittings Kits with Single Pump and Heat Exchanger - Traditional Models	30
PEX Fittings - 1" PEX	20	Sharkbite Fitting, Tee	25
PEX Hanger	21	Sharkbite Kit, Existing Boiler, Plate Exchanger	28
PEX Pipe Cutter	21	Slide Rod/Assemblies	41
Plate Exchangers	6	Slide Rod Plates	41
Plug, 1/2" PEX	20	Sludge Conditioner	39
Plug, 1" PEX	20	Solder & Soldering Flux	27
Plug, Pipe - MPT	24	Space Heater (100k Btu)	2
Plug, Pipe - Wrench Set	24	Space Heater (140k Btu)	2
Pump Cartridges	16	SuperPro Chimneys - 6" Diameter	37
Pump Panel Extension Kit - CleanFire 300/500	45	SuperPro Chimneys - 8" Diameter	37
Pump, Taco - 006 Series	14	SuperPro Chimneys (Selkirk)	37
Pump, Taco - 007 Series	14	Taco Switching Relay	17
Pump, Taco - 009 Series	14	Tape, Blue Teflon, 1/2" x 1429"	24
Pump, Taco - 0011 Series	15	Tee, Black	23
Pump, Taco - 014 Series	15	Tee, Brass	22
Pump, Taco - 0015e3™	16	Tee, Brass, 3/4"	22
Pump, Taco - Viridian® VR1816	15	Tee, Brass Diverter	27
Pump, Taco - Viridian® VT2218	15	Tee, Brass Offset, 4"	22
Push-fit - Depth Gauge/Deburring Tool	26	Tee, Brass - PEX	20
Push-fit - Disconnect Clip	26	Tee, Reducing - Copper	27
Push-fit - Disconnect Tongs	26	Tees, Copper	27
Push-fit Fitting - Adapter, Male	26	Tees, NPT	23
Push-fit Fitting - Connector, Straight	26		
Push-fit Fitting - Coupling, Reducing	26		
Push-fit Fitting - Female Adapter	26		

Alphabetical Index


Tempering Valve, Sweat	34
ThermoPEX Coupling Kit - 1" and 1-1/4"	10
ThermoPEX Coupling Kit - 25mm.	10
ThermoPEX Termination Cap	10
ThermoPEX with 1" or 1-1/4" PEX.	10
ThermoPEX with 25mm PEX	10
Thermostat, Line Voltage.	33
Thermostat, Plug-in	33
Tools - PEX	20
Torch, Outdoor	45
Transformer, 24-Volt	33
Twist-Lock Chimneys (Security).	38
Union, Brass Pipe - FIP.	22
Valve Bodies, Thermostatic Radiator	9
Valve Head, TRV II.	9
Valve, Radiant Mixing	36
Valve, Tempering	36
Valve, Water Heater Mixing.	36
Vent Valve, Automatic.	34
Water Heater Tube Kit	7
Water Sample Bottle Kit.	39
Water-to-Water Heat Exchanger for Domestic Water Heater	7
Y-Strainer	8
Zone Valves, Zone Sentry®	34

Heat Exchangers - Water-to-Air

IMPORTANT INFORMATION ABOUT BTU RATINGS:

Btu outputs and ranges are provided for comparison only. Actual Btu output will vary depending on a number of factors such as flow gpm, airflow cfm and water and air temperatures. Btu ratings assume high input factors and may not be achieved in actual installations and/or configurations with lower input factors.

Fan Convector (26k Btu)




Fan-forced convector. Quiet operation, integral filters and thermostat connections. 3/4" FPT fittings and on-off-thermostat switch. Output up to 26,000 Btu/hr. Color - taupe. 24-Volt Thermostat (p/n 588 or 8200008) is optional.

- 1971 Fan Convector, 26k Btu
- 588 Programmable 24-Volt Thermostat
- 8200008 Non-programmable 24-Volt Thermostat
- 956 Elbow, 90-degree, 3/4" x 3/4" FPT (optional)

Replacement Components

- 343 Snap Disc
- 342 Switch, ON/OFF
- 2500703 Fan Motor
- 340 Relay
- 2500010 Transformer

Fan Convector, Wall Mount (7k Btu)




Recessed wall, fan-forced convector. Quiet operation, integral filters and thermostat connections. Can use Female Adapter (p/n 6679) or Push-fit Fitting (p/n 606) for connection. 1/2" fittings and on-off-thermostat switch. Output up to 7,000 Btu/hr. 24-Volt Thermostat (p/n 588 or 8200008) is optional.

- 1941 Fan Convector, Wall Mount, 7k Btu
- 588 Programmable 24-Volt Thermostat
- 8200008 Non-programmable 24-Volt Thermostat

Replacement Components

- 343 Snap Disc
- 342 Switch, ON/OFF
- 1940 Fan Motor
- 340 Relay
- 2500010 Transformer

Fan Convector, Corner (7k Btu)




Fan-forced convector. Quiet operation, integral filters and thermostat connections. Can use Female Adapter (p/n 6679) or Push-fit Fitting (p/n 606) for connection. 1/2" fittings and on-off-thermostat switch. Output up to 7,000 Btu/hr. 24-Volt Thermostat (p/n 588 or 8200008) is optional.

- 1910 Fan Convector, Corner, 7k Btu
- 588 Programmable 24-Volt Thermostat
- 8200008 Non-programmable 24-Volt Thermostat

Replacement Components

- 343 Snap Disc
- 342 Switch, ON/OFF
- 1940 Fan Motor
- 340 Relay
- 2500010 Transformer


Fan Coil Unit, 50k Btu



50k Btu fan coil unit (3/4" FIP) includes housing, fan, heat exchanger coil and louvers. Btu range: 20k-50k Btu. Approximate dimensions: 16-1/4" x 17" x 13-1/4". Motor: 70 watts. Approximately 588 cfm.

- 2900544 Fan Coil Unit, 50k Btu
- 2900610 Replacement Fan, motor and shield, 50k Btu, for 29000544


Fan Coil Unit, 100k Btu



100k Btu fan coil unit (3/4" FIP) includes housing, fan, heat exchanger coil and louvers. Btu range: 40k-100k Btu. Approximate dimensions: 21" x 19" x 17". Motor: 180 watts. Approximately 1,352 cfm.

- 2900545 Fan Coil Unit, 100k Btu
- 2900611 Replacement Fan, motor and shield, 100k Btu, for 29000545

Fan Coil Unit, 220k Btu




220k Btu fan coil unit (3/4" FIP) includes housing, fan, heat exchanger coil and louvers. Btu range: 80k-220k Btu. Approximate dimensions: 31" x 18" x 25". Motor: 330 watts. Approximately 2,823 cfm.

- 2900546 Fan Coil Unit, 220k Btu
- 2900612 Replacement Fan, motor and shield, 220k Btu, for 29000546

Heat Exchangers - Water-to-Air


Space Heater (140k Btu)



Order the following components for a Space Heater (140k Btu). Some assembly required. Assembled size approximately 19" x 21" x 33".

- 415 Transition
- 154 Blower & Motor, 1/4-hp 3-speed fan
- 108 Heat Exchanger Coil, 140k Btu

Space Heater (100k Btu)




Order the following components for a Space Heater (100k Btu). Some assembly required. Assembled size approximately 19" x 21" x 33".

- 416 Transition
- 154 Blower & Motor, 1/4-hp 3-speed fan
- 106 Heat Exchanger Coil, 100k Btu

Heat Exchangers - Water-to-Air

Air Handler Cabinet




Two sizes allow multiple applications from 100k Btu to 220k Btu (refer to the chart for dimensions and heat exchanger coil ranges). Cabinets are standard with front water access; kits are available for converting to rear water access.

NOTE: Blower & Motor and Heat Exchanger Coil are sold separately. Air Handler Cabinet door is capable of holding a filter (not included). Some assembly will be required. If utilizing an existing 24-volt thermostat to control blower, a Fan Center Relay (p/n 515) must be used.

p/n	Dimensions (in.)	Heat Exch. Coil Range	Blower & Motor	Water Access
301	36 x 20 x 23 Filter (not included): 16 x 20	100k-140k Btu	1/4-hp	Front
303	39 x 25 x 28 Filter (not included): 20 x 20	185k-220k Btu	1-hp	Front

- 301 Air Handler Cabinet, 100k-140k Btu, front access
- 3822 Kit for 301 - back water access
- 303 Air Handler Cabinet, 185k-220k Btu, front access
- 3825 Kit for 303 - back water access

Blower & Motor



- 203 Blower & Motor, 1/15-hp
- 154 Blower & Motor, 1/4-hp, 3-speed fan
- 208 Blower & Motor, 1-hp, 3-speed fan

p/n 203 1/15 hp 115V	CFM (cubic feet per minute)							
	FREE AIR	1/8" SP	1/4" SP	3/8" SP	1/2" SP	3/4" SP	1" SP	1 1/4" SP
1530 rpm (1-speed)	465	430	397	357	308	N/A	N/A	N/A

p/n 154 1/4 hp 115V	CFM (cubic feet per minute)				
	FREE AIR	1/4" SP	1/2" SP	3/4" SP	1" SP
LOW speed	708	808	800	593	194
MED. speed	963	1063	1020	708	224
HIGH speed	1353	1349	1287	1014	250


p/n 208 1 hp 115V	CFM (cubic feet per minute)					
	1.2" SP	1.3" SP	1.4" SP	1.5" SP	1.6" SP	1.7" SP
LOW speed (1038 rpm)	2248	2143	2032	1890	1085	1498
MED. speed (1070 rpm)	2480	2373	2218	2084	1910	1696
HIGH speed (1097 rpm)	2701	2522	2373	2231	2057	1851

SP=static pressure, hp=horsepower

Heat Exchanger Coils


p/n	Output (Btu)	Approx. Plenum Size (in.)	Dimensions			3/4" FPT Outlets	1" Sweat Outlets
			Length (in.)	Width (in.)	Depth (in.)		
0020-041	75,000	16 x 18	17-1/2	15-1/4	5-1/2	-	Straight
0020-043	100,000	18 x 20	18-1/4	17-3/4	5-1/2	-	Straight
5600029	100,000	17 x 19	19	16-1/2	4-1/8	-	Straight
0020-044	125,000	18 x 22	20-1/4	18	5-1/2	-	Straight
0020-045	140,000	19 x 23	21	19	4-1/8	-	Straight
287	50,000	13 x 14	14	12-3/4	4-1/8	90°	-
109	80,000	13 x 18	18	12-3/4	4-1/8	Straight	-
102	95,000	15 x 20	20	15	4-1/8	Straight	-
106	100,000	17 x 19	19	16-1/2	4-1/8	Straight	-
107	125,000	18 x 20	20	17-3/4	4-1/8	Straight	-
704	125,000	18 x 20	20	17-3/4	4-1/8	90°	-
108	140,000	20 x 20	21	19	4-1/8	Straight	-
110	185,000	23 x 23	24	22-3/4	4-1/8	Straight	-
111	220,000	24 x 24	26	24	4-1/8	Straight	-

Water-to-air heat exchanger coils are available in different sizes with different Btu outputs. Be sure to check the dimensions of the coil and the approximate plenum size, in addition to the outlet configuration.



0020-044

Heat Exchanger Coil (100k Btu)




Heat Exchanger Coil (100k Btu) - Water-to-air heat exchanger coil with straight 1" sweat outlets. Used in forced-air furnaces with plenum size of approximately 17" x 18". Dimensions: 16-1/2" x 19" x 4-1/8".

5600029 Heat Exchanger Coil, 100k Btu, 1" Sweat

- 0020-041 Heat Exchanger Coil, 75k Btu (15-1/4"W x 17-1/2"L x 5-1/2"H) 1" Ports
- 0020-043 Heat Exchanger Coil, 100k Btu (17-3/4"W x 18-1/4"L x 5-1/2"H) 1" Ports
- 0020-044 Heat Exchanger Coil, 125k Btu (18"W x 20-1/4"L x 5-1/2"H) 1" Ports
- 0020-045 Heat Exchanger Coil, 140k Btu (19"W x 21"L x 5-1/2"H) 1" Ports

Heat Exchangers - Water-to-Air


Heat Exchanger Coil (50k Btu)



Water-to-air heat exchanger coil with 90° 3/4" female pipe thread (FPT) outlets. Dimensions: 12-3/4" x 14" x 4-1/8".

287 Heat Exchanger Coil, 50k Btu


Heat Exchanger Coil (80k Btu)



Heat Exchanger Coil (80k Btu) - Water-to-air heat exchanger coil with straight 3/4" FPT outlets. Used in forced-air furnaces with plenum size of approximately 13" x 18". Dimensions: 12-3/4" x 18" x 4-1/8".

109 Heat Exchanger Coil, 80k Btu


Heat Exchanger Coil (95k Btu)



Water-to-air heat exchanger coils with straight 3/4" FPT outlets. Used in forced-air furnaces with plenum size of approximately 15" x 18". Dimensions: 15" x 20" x 4-1/8".

102 Heat Exchanger Coil, 95k Btu


Heat Exchanger Coil (100k Btu)



Heat Exchanger Coil (100k Btu) - Water-to-air heat exchanger coil with straight 3/4" FPT outlets. Used in forced-air furnaces with plenum size of approximately 17" x 18". Dimensions: 16-1/2" x 19" x 4-1/8".

106 Heat Exchanger Coil, 100k Btu. 3/4" FPT


Heat Exchanger Coil (125k Btu)



Water-to-air heat exchanger coil with straight (p/n 107) or 90-degree (p/n 704) 3/4" FPT outlets. Used in forced-air furnaces with plenum size from approximately 18" x 18" to 18" x 20". Dimensions: 17-3/4" x 20" x 4-1/8".

107 Heat Exchanger Coil, 125k Btu, straight outlets
704 Heat Exchanger Coil, 125k Btu, 90° outlets


Heat Exchanger Coil (140k Btu)



Water-to-air heat exchanger coil with straight 3/4" FPT outlets. Used in forced-air furnaces with plenum size of approximately 20" x 20". Dimensions: 19" x 21" x 4-1/8".

108 Heat Exchanger Coil, 140k Btu


Heat Exchanger Coil (185k Btu)



Water-to-air heat exchanger coil with straight 3/4" FPT outlets. Used in forced-air furnaces with plenum size of approximately 23" x 23". Dimensions: 22-3/4" x 24" x 4-1/8".

110 Heat Exchanger Coil, 185k Btu

Heat Exchanger Coil (220k Btu)



Water-to-air heat exchanger coil with straight 3/4" FPT outlets. Used in forced-air furnaces with plenum size of approximately 24" x 24". Dimensions: 24" x 26" x 4-1/8".


111 Heat Exchanger Coil, 220k Btu

Plate Exchangers



- 0020-051 Plate Exchanger, 4.57" x 11.26"-20, 1" Port
 0020-052 Plate Exchanger, 4.57" x 11.26"-30, 1" Port
 0020-053 Plate Exchanger, 4.57" x 11.26"-50, 1" Port

Heat Exchanger, Plate



The Plate Heat Exchanger is a compact, high-performance, water-to-water, continuous flow heat exchanger with MPT ports. Units are 316L stainless, copper-brazed.


p/n	Typical Application
5600003	Water Heaters
5744	Boilers up to 100k Btu
5600001	Boilers 100k-175k Btu
5600002	Boilers 175k-250k Btu
5600019	Applications up to 760k Btu

- 5600003 Plate Exchanger, 5 x 12-6, 3/4" Port
 5744 Plate Exchanger, 5 x 12-30, 1" Port
 5600001 Plate Exchanger, 5 x 12-50, 1-1/4" Port
 5600002 Plate Exchanger, 5 x 12-70, 1-1/4" Port
 5600019 Plate Exchanger, 10 x 20-55, 1-1/4" Port

NOTE: Also see Swimming Pool Heat Exchangers (p/n 5600005 through 5600015).

Heat Exchangers - Water-to-Water


Mounting Bracket, Plate Heat Exchanger



Mounts most 5" x 12" Plate Heat Exchangers (30 or less) with mounting studs to a wall or similar surface.

- 5807-011 Plate Mounting Bracket


Mounting Kit, Plate Heat Exchanger



Mounts most 5x12 Plate Heat Exchangers (40 or more) with mounting studs to a wall or similar surface. Includes two mounting brackets.

- 2500299 Heat Exchanger Mounting Kit

Mounting Kit, Plate Heat Exchanger, 5x12, Universal




Universal mounting kit for 5x12 plate exchangers.

- 1097 Universal 5x12 Plate Heat Exchanger Mounting Kit

Heat Exchangers - Water-to-Water


Water-to-Water Heat Exchanger for Domestic Water Heater



The Water-to-Water Heat Exchanger is a stainless steel water-to-water, domestic water heat exchanger with 3/4" FIP end and side ports. Install on existing water heater for thermal circulating heat transfer. Fittings Kit (p/n 2053) or Push-fit Fittings Kit (9263) are available separately for easy installation.

5600018 Water-to-Water Heat Exchanger, 33"


Fittings Kit, Water Heater - for Water-to-Water Heat Exchanger



Used to install the Water-to-Water Heat Exchanger (p/n 5600018) on existing domestic water heater for thermal circulating heat transfer. Water-to-water heat exchanger is sold separately.

2053 Fittings Kit

Fittings Kit, Push-fit - for Water-to-Water Heat Exchanger



Used to install the Water-to-Water Heat Exchanger (p/n 5600018) on existing domestic water heater for thermal circulating heat transfer. Water-to-water heat exchanger is sold separately.


9263 Push-fit Fittings Water Heater Kit

Water Heater Tube Kit



0020-058 Water Heater Tube Kit

Heat Exchanger, Stainless 316L - for Swimming Pool



Stainless steel exchangers are used as hot tub or swimming pool heat exchangers. Other applications include snow melt or solar heating. **Not recommended for use with salt chlorinated pools or hot tubs.**

Mounting brackets are included for horizontal or vertical mounting. Should always be installed with the mounting bracket fixed to a wall, ceiling or floor to prevent damage from vibrations or water hammer.


p/n	Btu Rating	Pool Capacity (U.S. gallons)
5600005	55,000	3,960
5600006	155,000	11,900
5600007	300,000	23,800
5600008	360,000	29,000
5600009	600,000	47,500
5600010	1,200,000	95,100

Exchanger Dimensions

p/n	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)
5600005	7.6	13.3	2.5	1	3/4
5600006	9.2	15.9	3.1	1	1-1/2
5600007	20.5	27.6	3.1	1-1/2	2
5600008	28	35	3.1	1-1/2	2
5600009	25.4	33.9	4.3	2	2-1/2
5600010	25.9	35.2	5	2	2-1/2

5600005 Pool Heat Exchanger, 316L, 55k Btu
 5600006 Pool Heat Exchanger, 316L, 155k Btu
 5600007 Pool Heat Exchanger, 316L, 300k Btu
 5600008 Pool Heat Exchanger, 316L, 360k Btu
 5600009 Pool Heat Exchanger, 316L, 600k Btu
 5600010 Pool Heat Exchanger, 316L, 1200k Btu

Heat Exchanger, Titanium Grade 1 - for Swimming Pool



Mounting brackets are included

Ideal for swimming pools with salt water or where salt generator/chlorinators are used. Mounting brackets are included for horizontal or vertical mounting. Should always be installed with the mounting bracket fixed to a wall, ceiling or floor to prevent damage from vibrations or water hammer.

p/n	Btu Rating	Pool Capacity (U.S. gallons)
5600011	55,000	3,960
5600012	155,000	11,900
5600013	300,000	23,800
5600014	360,000	29,000
5600015	600,000	47,500

Exchanger Dimensions

p/n	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)
5600011	7.6	13.3	2.5	1	3/4
5600012	9.2	15.9	3.1	1	1-1/2
5600013	20.5	27.6	3.1	1-1/2	2
5600014	28	35	3.1	1-1/2	2
5600015	25.4	33.9	4.3	2	2-1/2

- 5600011 Pool Heat Exchanger, Titanium Grade 1, 55k Btu
- 5600012 Pool Heat Exchanger, Titanium Grade 1, 155k Btu
- 5600013 Pool Heat Exchanger, Titanium Grade 1, 300k Btu
- 5600014 Pool Heat Exchanger, Titanium Grade 1, 360k Btu
- 5600015 Pool Heat Exchanger, Titanium Grade 1, 600k Btu

Mounting Brackets - Swimming Pool Heat Exchangers



Replacement mounting brackets for Stainless 316L and Titanium Swimming Pool Heat Exchangers.

- 3104665 Mounting Bracket, 55k Btu Pool Heat Exchangers
- 3104940 Mounting Bracket, 155k/300k/360k Btu Pool Heat Exchangers
- 3104941 Mounting Bracket, 600k Btu Pool Heat Exchangers
- 3104942 Mounting Bracket, 1200k Btu Pool Heat Exchangers


Heat Exchangers - Water-to-Water

Filter & Fill Valve Kits



- 2500704 Fill Valve and Inline Filter, Kit, Push-fit
- 0020-325 Fill Valve and Inline T-Strainer, Crimp
- 0020-261 Filter, Inline Screen - 1" FPT - Black

Y-Strainer



Y-Strainer with 0.20 mesh and FIP fittings. Recommended when installing plate-style heat exchangers. For 3/4" Y-Strainer, use 1/2" Brass Pipe Plug (p/n 6557) for cleanout port. For 1" Y-Strainer, use 3/4" Brass Pipe Plug (p/n 574) for cleanout port.


- 1694 Y-Strainer, 1-1/4" - Black
- 1695 Y-Strainer, 3/4" - Brass

Heat Exchangers - Convection

Radiant Baseboard Heaters, Complete




Kickspace Heaters



Myson Whispa™ III Kickspace 9000 fan-forced convector, output of 7,634-9,949 Btu/hr. Dimensions: 17-3/4" x 12-1/8" x 3-5/8". Weight: 15 lb. Fan speed (cfm): boost - 124, normal - 82. Cover grill is 4" x 23-3/4".

- 5600000 Myson Whispa III Kickspace 9000 Fan Convector
- 0020-089 Wall Mount Kit, Surface - Kickspace Heater (not shown)

Valve Bodies, Thermostatic Radiator



Each valve body is threaded for nominal iron pipe threads and also comes with a compression nut and ferrule. Replacement head only is part number 5000378.

- 604 TRV II Valve Body and Head, 1/2" Vertical
- 5000851 LKD Valve, 1/2" Preset Flow Rate

Valve Head, TRV II



Replacement valve head for 604 TRV II Valve Body and Head, 1/2" vertical.

- 5000378 Valve Head, 1/2" Vertical, TRV II

Piping - ThermoPEX

ThermoPEX with 1" or 1-1/4" PEX



ThermoPEX is flexible pre-insulated piping consisting of two waterproof oxygen barrier PEX-A lines (supply and return) protected by polyurethane closed cell foam insulation and a thick, durable, waterproof polyethylene outer jacket. It is the ideal insulated piping for use with outdoor wood furnaces. The outside diameter of 1" ThermoPEX is 4-3/8"; 1-1/4" ThermoPEX has an outside diameter of 5".

Available with 1" Central PEX in 100-ft, 200-ft or 800-ft rolls, or with 1-1/4" PEX in 100-ft or 300-ft rolls.


2441	ThermoPEX, 1", 100' Roll
5700034	ThermoPEX, 1", 200' Roll
2491	ThermoPEX, 1", 800' Roll
2799	ThermoPEX, 1-1/4", 100' Roll
2492	ThermoPEX, 1-1/4", 300' Roll

ThermoPEX Coupling Kit - 1" and 1-1/4"




Twelve-inch rubber splice is used to join two ends of ThermoPEX together. Includes band clamps. Fittings and crimp rings for joining the PEX lines are sold separately.

NOTE: Do NOT use 1330 or 1331 PEX Adapters with ThermoPEX Coupling Kits as the barb on these adapters is too short for underground splices. Use 5642 or 5643 Brass Clamp Fittings.



2447	ThermoPEX Coupling Kit, 1"
2495	ThermoPEX Coupling Kit, 1-1/4"
5642	Brass Clamp Fittings, 1"
5643	Brass Clamp Fittings, 1-1/4" PEX Pipe (SDR-11)
1333	PEX Coupling, 1"

ThermoPEX with 25mm PEX




ThermoPEX with two 25mm waterproof oxygen barrier PEX-A lines (supply and return) is more flexible and easier to haul and ship. It's ideal for shorter runs and for the do-it-yourselfers. The outside diameter of 25mm ThermoPEX is 2-15/16".

The 55' roll (p/n 5700047) is UPS shippable. All rolls except the 500' roll can be shipped via Spee-Dee.

5700047	ThermoPEX, 25mm, 55' Roll
5700043	ThermoPEX, 25mm, 60' Roll
5700046	ThermoPEX, 25mm, 95' Roll
5700045	ThermoPEX, 25mm, 500' Roll

ThermoPEX Coupling Kit - 25mm



Twelve-inch rubber splice is used to join two ends of ThermoPEX together. Includes band clamps. Fittings and crimp rings for joining the PEX lines are sold separately.

2500172	ThermoPEX Coupling Kit, 25mm
---------	------------------------------

ThermoPEX Termination Cap



Fits snugly over each end to protect and seal the insulation from water. Includes band clamps.

5500014	ThermoPEX Cap, 25mm
2443	ThermoPEX Cap, 1"
2494	ThermoPEX Cap, 1-1/4"

Piping - EZ Lay and 1-1/4" PEX Crimp Fittings

EZ Lay Insulated Pipe

Water lines are insulated with commercial-grade EPS insulation in a 4" (5" for 5-wrap pipe) commercial-grade corrugated tile. Includes one blue PEX line, one red PEX line, two end caps and string for pulling an electrical, thermostat or tracing wire through the corrugated tile.

Available in rolls or by the foot (see part numbers for prices per foot). The 5-wrap pipe is only available by the foot. When ordering by the foot, please be sure to add 5 feet on each end when measuring the distance needed for the pipe.



1" PEX Lines - 3-Wrap

- 0020-651 EZ Lay 3-wrap Insulated Pipe (regular non-barrier), 1" - per foot
- 0020-655 EZ Lay 3-wrap Insulated Pipe, (oxygen barrier) 1" - per foot

1-1/4" PEX Lines - 3-Wrap and Fittings

- 0020-653 EZ Lay 3-wrap Insulated Pipe, 1-1/4" - per foot

Fittings, 1-1/4" PEX (CTS)

The 1-1/4" PEX lines in the EZ Lay are 1-1/4" CTS (copper tubing size), SDR-9; fittings here are for 1-1/4" CTS.



- 0020-576 PEX 90° Crimp Elbow, 1-1/4"




- 0020-578 PEX Crimp Plug, 1-1/4"

1" PEX Lines - 5-Wrap




- 0020-656 EZ Lay 5-wrap Insulated Pipe, 1" - per foot

PEX Tubing Technical Specifications




1/2" CTS

Central PEX / PureLink / HeatLink
SDR = 9



1" CTS

ThermoPEX / Central PEX / E-Z Lay Pipe
SDR = 9




1-1/4" CTS

E-Z Lay Pipe
SDR = 9

PEX Tubing Size (CTS/Nominal)	Outside Diameter (OD)	Minimum Wall Thickness	Inside Diameter (ID)
1/2"	0.625"	0.070"	0.485"
1"	1.125"	0.125"	0.875"
1-1/4"	1.375"	0.153"	1.069"


Notes:

1. PEX tubing sizes are denoted by CTS (copper tubing size), not OD (Outside Diameter) or ID (Inside Diameter).
2. OD of PEX, copper and CPVC pipe with the same size (CTS) is the same. This is why push fittings can be used with all of these pipes.
3. PEX made to US standards must comply with a SDR-9 (Standard Dimension Ratio), which is the ratio of OD (Outside Diameter) to pipe wall thickness (9:1). Exceptions are nominal sizes 1/2" and below.



25mm

ThermoPEX
SDR = 11



1-1/4"

ThermoPEX / Central PEX
SDR = 11

PEX Tubing Size (Nominal)	Outside Diameter (OD)	Minimum Wall Thickness	Inside Diameter (ID)
25mm	0.990"	0.091"	0.809"
1-1/4"	1.583"	0.146"	1.29"


Notes:

1. PEX with a SDR-11 (Standard Dimension Ratio) are NOT compatible with CTS (copper tubing size) fittings.
2. 25mm PEX and 1-1/4" PEX used in ThermoPEX are SDR-11 (Standard Dimension Ratio), which is the ratio of OD (Outside Diameter) to pipe wall thickness (11:1).

Piping - Fittings

Central PEX 1" Pipe


High-density, non-oxygen barrier PEX-B, cross-link pipe, rated for temperatures to 180°F at 100 psi. Note that color has changed from green to red.



1311	Central PEX 1" Pipe, 100'
1312	Central PEX 1" Pipe, 200'
1313	Central PEX 1" Pipe, 300'
1314	Central PEX 1" Pipe, 500'


Central PEX 1" Pipe Sections

Central PEX 1" Pipe, non-oxygen barrier PEX-B, in straight 8-ft sections.



5700082	Central PEX 1" Pipe, 8' straight section, 10 per bag
5700083	Central PEX 1" Pipe, 8' straight section, 25 per bag

PEX 1-1/4" Pipe (SDR-11)




High-density, oxygen barrier PEX-A, cross-link pipe, rated for 180°F.

NOTE: This PEX is SDR-11 and is not compatible with 1-1/4" CTS fittings. Use only Brass Fittings (p/n 380, 381 and 382) or Brass Clamp Fitting (p/n 5643) for this 1-1/4" PEX Pipe.

5670	PEX 1-1/4" Pipe, 150'
386	PEX 1-1/4" Pipe, 328'

Fittings, Brass - for 1-1/4" PEX Pipe (SDR-11)



Brass fittings for 1-1/4" PEX pipe (SDR-11). To ease installation, it is recommended that a heat gun be used on the 1-1/4" PEX pipe. Not compatible with 1-1/4" CTS PEX.

380	Male Adapter, 1-1/4" barb x 1-1/4" MIP
381	Brass Coupling, 1-1/4" barb x 1-1/4" barb
382	Brass Elbow, 1-1/4" barb x 1-1/4" barb


Clamp, Hose, 1" or 1-1/4" (SDR-11)



1" or 1-1/4" (SDR-11) stainless steel hose clamp.

5978	Hose Clamp, 1"
1745	Hose Clamp, 1-1/4"

Fittings, PEX



Brass adapter clamps for PEX pipe.

5642	Brass Clamp Fittings, 1"
5643	Brass Clamp Fittings, 1-1/4" PEX Pipe (SDR-11)

Coupling, 25mm PEX



For coupling two 25mm Central PEX pipe ends.

5000462	PEX Coupling, 25mm
---------	--------------------

Couplings, 1/2" and 1" PEX



For coupling two Central PEX pipe ends.

1339	PEX Coupling, 1/2"
1333	PEX Coupling, 1"

Grundfos UPMS 20-78 F Circulator



Grundfos UPMS is a high-efficiency ECM variable-speed circulator that can be used as an integrated circulator pump in systems designed for a wide variety of heating applications. The pump features robust startup, self-venting ability and dry-running protection leading to fewer callbacks after installation.

- Speed-controlled, high-efficiency pump fitted with electronically commutated motor (ECM) with permanent magnet rotor and frequency converter.
- Next generation ECM pump designed to integrate with heat sources for better system efficiencies.
- Intuitive user interface.
- Three settings for constant curve.

Amp (max.)	Watt	Head (ft)	Volume (gal/min)
1.25 @ 68W	2-68	25.6	16

5800056 Grundfos UPMS 20-78 F Circulator

Grundfos UPMS 20-58 F Circulator




Grundfos UPMS is a high-efficiency ECM variable-speed circulator that can be used as an integrated circulator pump in systems designed for a wide variety of heating applications. The pump features robust startup, self-venting ability and dry-running protection leading to fewer callbacks after installation.

- Speed-controlled, high-efficiency pump fitted with electronically commutated motor (ECM) with permanent magnet rotor and frequency converter.
- Next generation ECM pump designed to integrate with heat sources for better system efficiencies.
- Intuitive user interface.
- Three settings for constant curve.

Amp (max.)	Watt	Head (ft)	Volume (gal/min)
0.71 @ 38W	8.4-38	19	13.6

5800055 Grundfos UPMS 20-58 F Circulator

Pump, Taco - 006 Series



Taco 006 Bronze Circulation Pump for domestic water systems. No flange required, 3/4" sweat connection. Power Supply Cord (p/n 556) sold separately.

size	hp	Amp	Watt	Head (ft)	Volume (gal/min)
006	1/40	0.52	59.8	9	10

175 Taco 006 Bronze Pump

Pump, Taco - 007 Series




The Taco 007 circulator pump is one of the industry's top-selling hydronic circulators, and for good reason. It features a unique cartridge design that's completely field serviceable plus a self-lubricating system that's virtually maintenance-free. Includes O-rings. Power Supply Cord (p/n 556) sold separately.

size	hp	Amp	Watt	Head (ft)	Volume (gal/min)
007	1/25	0.70	80.50	11	20
007 Priority	1/25	0.70	81.65	11	20

5800004 Taco 007 Circulating Pump

5800011 Taco 007 Priority Pump

Pump, Taco - 009 Series



Taco 009 Circulation Pumps require flange kit (not included). Includes O-rings. Power Supply Cord (p/n 556) sold separately.

size	hp	Amp	Watt	Head (ft)	Volume (gal/min)
009	1/8	1.40	161	34	8

5800006 Taco 009 Pump

Circulators

Pump, Taco - 0011 Series



The Taco High Velocity Series 0011 Cartridge Circulator is specifically designed for high-head/medium-flow applications in large residential/light commercial closed-loop hydronic heating systems. Power Supply Cord (p/n 556) sold separately.

size	hp	Amp	Watt	Head (ft)	Volume (gal/min)
0011	1/8	1.76	202.4	31	31

0020-351 Taco 0011 Circulating Pump

Pump, Taco - 014 Series



Taco 014 Circulation Pumps require flange kit (not included). Includes O-rings. Power Supply Cord (p/n 556) sold separately.

size	hp	Amp	Watt	Head (ft)	Volume (gal/min)
014	1/8	1.55	178	22	32

5800008 Taco 014 Pump

Pump, Taco - Viridian® VT2218




The Taco Viridian VT2218 pump is a temperature sensing, variable speed wet rotor circulator with an ECM permanent magnet motor. Operating modes include Delta-T differential temperature, 4 fixed speeds, set point heat, set point cool and boiler protection.

- Delta-T operation maximizes system efficiency and comfort
- High-efficiency ECM motor uses up to 85% less electricity
- LCD displays operating mode, temperature or speed setting, watts, supply & return temperatures
- Easy to program and install
- 110-120V, 50/60 Hz single phase
- 1650-4200 RPM

Model	Max. Amp	Watt	Max. Shutoff Head (ft)	Max. Flow (gal/min)
VT2218F	0.67	9-58	22	18
5800025	Taco Viridian Pump, VT2218			
5800041	Replacement Temperature Sensor			

Pump Cartridges



- | | |
|---------|---|
| 222 | Replacement Cartridge, 006 Series Pumps |
| 5800005 | Replacement Cartridge, Taco 007 Pump |
| 5800007 | Replacement Cartridge, 009 Series Pumps |
| 5800010 | Replacement Cartridge, Bronze, 011 Series Pumps |
| 5800009 | Replacement Cartridge, Bronze, 014 Series Pumps |

Replacement Seal Kits and Gaskets


- | | |
|----------|--|
| 5800034 | O-Ring, Cartridge, Taco 007/009 (set of 2) |
| 0020-346 | Replacement Seal Kit, Taco 2400-20 pump |



Compatible with Taco 007 series of pumps.

- | | |
|-----|------------------------------|
| 542 | O-Ring Set, Taco Pump Flange |
|-----|------------------------------|


Flanges, Pump



Each kit includes set of two female iron pipe (FIP) pump flanges. One set is used with each pump. Most installations use Pump Flange Kit, 3/4" (p/n 119).

- | | |
|---------|-------------------------|
| 119 | Pump Flange Kit, 3/4" |
| 194 | Pump Flange Kit, 1" |
| 5800019 | Pump Flange Kit, 1-1/4" |

Flange Kit, Isolation



Kit includes flanges, nuts and bolts. Full port, valved flange body.

- | | |
|-----|----------------------------------|
| 224 | "Free Floating" Flange Kit, 3/4" |
| 225 | Isolation Flange Kit, 1-1/4" |



- | | |
|----------|----------------------------------|
| 0020-365 | Gasket, Isolation Flanges (each) |
|----------|----------------------------------|




- | | |
|----------|---------------------------|
| 0020-366 | Pump Isolation Flange, 1" |
|----------|---------------------------|

NOTE: Price is for one flange only.

Circulators & Related

Flange, 3/4" Isolation - with Drain Valve



Includes flange, nuts and bolts.

226 Isolation Flange with Drain Valve, 3/4"

NOTE: Price is for one flange only.


Cord, Power Supply



May be used to wire pumps when installed on furnaces. Power Supply Cord includes strain relief.

555 Power Supply Cord, 48"

Mount Kit, Wall - Pump



Brackets for supporting and securing pump and flanges to a wall. Figure shows one possible installation scenario. Pump, flanges and mounting hardware are not included.

1366 Pump Wall Mount Kit


Taco Switching Relay



The SR501 single zone switching relay can easily replace any brand made by any manufacturer, and will even fit into the existing metal enclosure without rewiring incoming connections. The SR501 single zone switching relay is UL and CSA listed, uses a standard "ice cube" replaceable relay and is compatible with conventional and programmable thermostats. External indicator lights provide instant diagnostic feedback, making a snap of service calls or new installation start-ups.

8200291 Taco Switching Relay

Manifold Kits



4-Loop shown for illustration purposes

Commonly used for radiant floor heat systems, stainless steel radiant manifold kits are available in various loop configurations for use with 1/2" PEX*.

Each kit includes:

- See-through body flow meters with adjustable flow rates
- Isolation ball valves with 1" NPT fitting
- Temperature gauge for each isolation valve
- Automatic float vent
- 1/2" PEX compression connectors*
- Mounting brackets

2900552	Manifold Kit, 2-Loop
2900553	Manifold Kit, 3-Loop
2900554	Manifold Kit, 4-Loop
2900556	Manifold Kit, 6-Loop
2900558	Manifold Kit, 8-Loop
2900560	Manifold Kit, 10-Loop
2900562	Manifold Kit, 12-Loop
5000673	O-ring, Manifold

Manifold Kit Connectors



For use with Stainless Steel Radiant Manifold Kits.

2900563	Connector, Compression, 1/2" PEX
2900564	Connector, Compression, 1/2" PEX-AL-PEX - ONLY FOR ALUMINUM CORE PEX

Adapter, Female 1" NPT - for Manifold Kits



For use with Stainless Steel Radiant Manifold Kits.

2900614	Adapter, Manifold, Female 1" NPT
---------	----------------------------------

Cap - for Manifold Kits



Manifold Loop Cap can be used with Stainless Steel Radiant Manifold Kits.

2900551	Loop Cap, Manifold
---------	--------------------


Gauge, Temperature - for Manifold Kits



Manifold Temperature Gauge can be used with Stainless Steel Radiant Manifold Kits.

2900596	Temperature Gauge, Manifold
---------	-----------------------------

Actuator, Thermal




Optional Thermal Actuator (compatible with Stainless Steel Radiant Manifold Kits) is available with either 2-wire or 4-wire configuration. 2-wire provides individual loop flow control on multi-zoned manifold. 4-wire also features end switch for activation of a pump.

2900549	Thermal Actuator, 2-wire
2900550	Thermal Actuator, 4-wire

HeatLink Products


Central PEX 1/2" Pipe

High-density, oxygen barrier PEX-B, cross-link pipe. Rated for temperatures to 180°F at 100 psi. Available in rolls up to 1000 ft long. Excellent for radiant floor heating applications.



1320	Central PEX 1/2" Pipe, 300'
1321	Central PEX 1/2" Pipe, 500'
1322	Central PEX 1/2" Pipe, 1000'

Mixing Valve, 4-way FNPT



This unit mixes high-temperature boiler water with heated return water to create tempered water for radiant systems and other applications. It is manually operated.

64026	Mixing Valve, 1" x 4-way FNPT
64031	Mixing Valve, 1-1/4" x 4-way FNPT

Adapters, PEX - Threaded Pipe



For adapting threaded pipe to Central PEX pipe.

1341	PEX Adapter, 1/2" PEX x 1/2" MIP fittings
1336	PEX Adapter, 1/2" PEX x 3/4" MIP fittings
1330	PEX Adapter, 1" PEX x 3/4" MIP fittings
1324	PEX Adapter, 1" PEX x 1" MIP fittings

Adapters, PEX - Copper Pipe



For adapting copper pipe to Central PEX pipe. NOTE: The 1331 PEX Adapter can also be used for 3/4" sweat applications by sweating the fitting inside.

1337	PEX Adapter, 1/2" PEX x 1/2" sweat fitting
1331	PEX Adapter, 1" PEX x 3/4" or 1" sweat fitting
1348	PEX Adapter, 1/2" PEX x 1/2" FIP fitting
5000651	PEX Adapter, 1" PEX x 1" sweat fitting

Adapter, Brass PEX - Threaded Pipe



5000464	Brass PEX Adapter, 25mm x 3/4" FPT
---------	------------------------------------

Elbow, PEX 90° Swoop



1" stainless steel PEX 90° swoop (sweep) elbow.

5000768	PEX Swoop Elbow, 90°
---------	----------------------

Adapter, Female - Copper Pipe



Adapts 1/2" copper pipe to 1/2" Central PEX pipe. Sweat end fits over copper pipe.

6679	Female Adapter, 1/2" barb x 1/2" sweat fittings
------	---

Elbow, PEX 90°



For coupling two Central PEX pipe ends together.

1340	PEX 90° Elbow, Brass, 1/2"
1334	PEX 90° Elbow, Brass, 1"

Elbow, Brass PEX 90° - Threaded Pipe



For coupling 1" Central PEX pipe to 3/4" MPT threaded pipe.

5000531	Brass PEX Adapter, 1" PEX x 3/4" MPT fittings, 90° Elbow
---------	--

Tee, Brass - PEX



Brass tee for joining Central PEX pipe ends.

1338	PEX Tee, 1/2"
1332	PEX Tee, 1"

Tools - PEX

0020-147



0020-147	Crimp Tool, 3/8" x 1" Compact Combination
----------	---

PEX Fittings - 1" PEX


1335



5000557



0020-150



5000661

1335	Crimp Ring, 1" PEX
5000557	Ball Valve, 1" PEX x 1" PEX, Full Port
0020-150	PEX Coupling, 1" FPT Swivel x 1" PEX
5000661	Ball Valve, 1" FIP

Clamp Crimp Ring, PEX Stainless Steel



For use with Central PEX pipe. Install with Cinch Tool (p/n 5925) or Ratchet Cinch Tool (p/n 4472).

5000465	PEX Stainless Steel Clamp Crimp Ring, 25mm
5927	PEX Stainless Steel Clamp Crimp Ring, 1/2"
5926	PEX Stainless Steel Clamp Crimp Ring, 1"

Plug, 1/2" PEX



Brass crimp plug for 1/2" PEX.

5000784	Plug, 1/2" PEX Crimp
---------	----------------------

Plug, 1" PEX




Brass crimp plug for 1" PEX.

5000785	Plug, 1" PEX Crimp
---------	--------------------

Fittings and Tools - PEX


Cinch Tool



Tool for cinching 1" and 1/2" PEX Stainless Steel Clamp Crimp Rings to PEX pipe. Not for use with any other application.

5925 Cinch Tool


PEX Pipe Cutter



Designed for smooth, even cutting, the tool's jaw fits firmly over the pipe for a square, burr-free cut.

2900619 PEX Pipe Cutter


Ratchet Cinch Tool



Compact, easy-to-use Ratchet Cinch Tool comes with calibrating device. For use with 5927, 5926 and 5000465 crimp rings.

4472 Ratchet Cinch Tool


Clamp Crimp Ring Removal Tool



Used to remove PEX stainless steel clamp crimp rings (p/n 5927, 5926 and 5000465).

2900737 Clamp Crimp Ring Removal Tool

PEX Hanger




Half-moon, nail-in PEX Hanger for securing PEX piping. Available in two sizes.

293 PEX Hanger, 1/2"

295 PEX Hanger, 1"

Crimp Tool, Universal



Used to crimp terminals. For 14-24 AWG wires.

2900341 Universal Crimp Tool, 14-24 AWG

Union, Brass Pipe - FIP



Suggested for use with plate-style heat exchanger installations.


5907	Brass Pipe Union, 3/4"
5908	Brass Pipe Union, 1"
5909	Brass Pipe Union, 1-1/4"

Coupler, Brass



0020-185	Brass Coupler, 1" FPT
5367	Brass Coupling, 3/4" thread

Nipple, Brass



Brass nipples in varying lengths.


535	Nipple, Brass, 3/4" x 2"
536	Nipple, Brass, 3/4" x 7"
5000394	Nipple, Brass, 3/4" x 4"
0020-186	Brass Nipple, 1" Short

Tee, Brass



0020-187	Brass Tee, 1" FPT
----------	-------------------


Tee, Brass, 3/4"



Brass Tee, 3/4" male x female x male. Mainly used for installing heat exchanger on water heater when push-fit fittings are used.

9624	Tee, Brass, 3/4"
------	------------------

Tee, Brass Offset, 4"



Can be used in conjunction with the Temperature Gauge (p/n 174 or p/n 6054) for monitoring furnace supply water temperature, or may be used instead of Nipple (p/n 533) and 90° Street Elbow (p/n 274) on supply and/or return bung.

6764	Brass Offset Tee, 4"
------	----------------------

Reducer Bushing, Brass



0020-188	Brass Reducer Bushing, 1" x 1/2"
0020-189	Brass Reducer Bushing, 1-1/4" x 1"
0020-192	Brass Reducer Bushing, 3/4" to 1"
385	Brass Hex Bushing, 1-1/2" x 3/4"
3851	Brass Hex Bushing, 1-1/4" x 3/4"
3042	Brass Hex Bushing, 1/2" x 1/8"

Elbow, Brass



0020-190	Brass Street 90° Elbow, 1"
0020-194	Brass 90° Elbow, 1" FPT

Adapter, Brass



0020-195	Brass Adapter, 1/2" MIP x 3/4" FPT Hose Bib
----------	---

Adapter, Female, 3/4" Hose, Brass



4928	Brass Adapter, 3/4" female hose x 3/4" male pipe
------	--

Adapter, Male, 3/4" Hose, Brass



4929	Brass Adapter, 3/4" male hose x 3/4" male pipe
------	--

Adapter, 1" Crimp x 1" FPT

0020-161	Adapter, 1" Crimp x 1" FPT
----------	----------------------------


Fittings - Threaded

Nipple, Black



0020-250	Nipple, Black, 1" x 2"
0020-251	1" x 3" Black Nipple
0020-252	Nipple, Short Black, 3/8" x 1-1/2"

Nipple, Close - Black



Nipple (p/n 118) is used with pumps and ball valves. All nipples listed here are Schedule 80, extra heavy.

118	Nipple, 3/4" x close, Schedule 80, extra heavy
409	Nipple, 1-1/4" x close, Schedule 80, extra heavy
314	Nipple, 1-1/2" x close, Schedule 80, extra heavy

Nipple, Brass Close



Brass Nipple with 3/4" MPT x close fittings.

270-0049 Nipple, Brass, 3/4" x close

Tee, Black

0020-255	Tee, Black, 1"
----------	----------------

Reducer Bushing, Black



0020-257	Reducer Bushing, Black, 3/4" x 1"
0020-258	Reducer Bushing, Black 1-1/2" x 1"
0020-259	Reducer Bushing, Black, 3/8" x 1/2"
0020-260	Reducer Bushing, Black, 1" x 1/2"

Bushing, Hex - NPT



Hex bushing with national pipe threads (NPT).

180	Hex Bushing, 3/4" x 1/8"
388	Hex Bushing, 1-1/4" x 3/4"
408	Hex Bushing, 1-1/2" x 1-1/4"

Tees, NPT



Black Tee (p/n 133) can be used for vent option near pump. Brass Tee (p/n 3850) can be used in domestic water situations. Black Tee (p/n 418) can be used to install 1-1/4" thermostatic valve.

133	Tee, Black, 3/4" NPT
3850	Tee, Brass, 3/4" NPT
418	Tee, Black, 1-1/4" NPT

Elbow, 45° Street



NPT 45° Street Elbow (black).

124	45° Street Elbow, 3/4"
5000017	45° Street Elbow, 1-1/4"

Elbow, 90° Street



90° Street Elbow in different sizes.

411	90° Street Elbow, 1-1/4"
274	90° Street Elbow, 3/4"
126	90° Street Elbow, Brass, 3/4"

Elbow, 90° - FPT



90° Elbow with female threads.

956	90° Elbow, 3/4" x 3/4" FPT
5000016	90° Elbow, Black, 1-1/4"

Caps, Round Pipe



332	3/4" Round Pipe Cap
333	1-1/4" Round Pipe Cap


Plug, Pipe - MPT



Pipe Plug, MPT, black, unless noted.

331	Pipe Plug, 3/4"
574	Pipe Plug, Brass 3/4"
383	Pipe Plug, 1-1/4"
6557	Pipe Plug, Brass 1/2"


Plug, Pipe - Wrench Set



Large end is for 1-1/4"; small end fits 3/4" pipe plugs.

5459	Pipe Plug Wrench Set
------	----------------------


Gauges, Temperature



In-line, dial temperature gauge with 1/2" MPT (p/n 174) is optional for manifold, pool heater systems, etc. Gauge (p/n 6054) is 1/8" MPT, 1" diameter with 1" stem length, for use in tight areas.

6054	Temperature Gauge, 1/8" MPT
174	Temperature Gauge, 1/2" MPT

Tape, Blue Teflon, 1/2" x 1429"



Compatible with a broad range of piping materials. Will not harden or crack on joint. Acts as a thread lubricant and anti-seize. No curing time, unlimited shelf life.

10713	Tape, Blue Teflon, 1/2" x 1429"
-------	---------------------------------

Fittings - Sharkbite

Sharkbite Fittings

Reducer Coupling



MPT Adapter



Elbow



Tee



Coupling



Female Adapter

Sharkbite Fittings - Coupling, Straight

0020-501 Sharkbite Coupling, 3/4"

0020-502 Sharkbite Coupling, 1"

Sharkbite Fitting - Coupling, Reducing

0020-503 Sharkbite Reducer Coupling, 3/4" x 1/2"

0020-530 Sharkbite Coupling, Reducing, 1/2" x 3/4" MNPT

0020-532 Sharkbite 90° Elbow, Reducing, 3/4" x 1/2"

Sharkbite Fitting - Female Adapter

0020-505 Sharkbite Adapter, 1/2" Female

0020-506 Sharkbite Adapter, 3/4" Female

0020-507 Sharkbite Adapter, 1" Female

Sharkbite Fitting - Adapter, Male

0020-509 Sharkbite Adapter, 3/4" MPT

0020-510 Sharkbite Adapter, 1" MPT

Sharkbite Fittings, Elbow

0020-511 Sharkbite Elbow, 1/2"

5000786 Sharkbite Elbow, 3/4"

0020-513 Sharkbite Elbow, 1"

Sharkbite Fitting, Tee


0020-515 Sharkbite Tee, 1/2"

0020-517 Sharkbite Tee, 1"

Sharkbite Ball Valve

0020-544 Sharkbite Ball Valve, 1"

Push-fit Fittings - Coupling, Straight



- 606 Push-fit Coupling, Straight, 1/2" x 1/2"
- 607 Push-fit Coupling, Straight, 3/4" x 3/4"
- 608 Push-fit Coupling, Straight, 1" x 1"

Push-fit Fitting - Coupling, Reducing




- 609 Push-fit Coupling, Reducing, 1" x 3/4"

Push-fit Fitting - Female Adapter




- 611 Push-fit Female Adapter, 1" x 1" FPT

Push-fit Fitting - Adapter, Male



- 612 Push-fit Male Adapter, 1" x 3/4" MPT

Push-fit Fitting - Connector, Straight



- 9264 Push-fit Connector, Straight, 3/4" x 3/4" MIP

Push-fit Fittings, Elbow



- 613 Push-fit Elbow, 1" x 1"
- 9265 Push-fit Elbow, 3/4" x 3/4"

Push-fit Fitting, Tee



- 614 Push-fit Tee, 1" x 1" x 1"

Push-fit Fitting - Temperature Gauge



1/8" MPT Temperature Gauge (p/n 6054) installs on Temperature Gauge Fitting and fitting installs on push-fit fitting Tee (p/n 614).

- 1350 Push-fit Temperature Gauge Fitting, 1" x 1/8" NPT

Push-fit - Depth Gauge/Deburring Tool



Deburs pipe and used to mark pipe to indicate when the pipe is inserted completely into the fitting. One tool for 1/2", 3/4" and 1" pipe.

- 615 Push-fit Depth Gauge/Deburring Tool

Push-fit - Disconnect Clip



Used to disconnect push-fit fittings quickly and easily.

- 616 Push-fit Disconnect Clip, 1/2"
- 617 Push-fit Disconnect Clip, 3/4"
- 618 Push-fit Disconnect Clip, 1"

Push-fit - Disconnect Tongs



0020-534
0020-536

- 0020-534 Push-fit Disconnect Tongs, 1/2"
- 0020-536 Push-fit Disconnect Tongs, 1"

Fittings - Copper/Sweat

Cap, Copper End



376 Copper End Cap, 1" sweat fitting

Elbow, Vent - Copper



372 Vent Elbow, 3/4" x 3/4" sweat fittings

Reducer, Copper



231 Reducer, Copper Pipe, 1" x 3/4" sweat fittings

Elbow, 90° Reducing - Copper



123 90° Reducing Elbow, 1" x 3/4" sweat fittings


Elbow, 90° - Copper



276 90° Elbow, 3/4" x 3/4" sweat fittings

277 90° Elbow, 1" x 1" sweat fittings

Tee, Brass Diverter



The diverter tee is an excellent sweat fitting used mainly with fan-forced heaters.

6782 Brass Diverter Tee, 1" x 1" x 1/2" sweat


Elbow, 90° Street - Copper



90° street elbow with 1" female sweat fitting on one end and 1" male sweat fitting on the other.

103 Street Elbow, 1"

Couplings, Copper



146 Copper Coupling, 3/4" sweat x 3/4" sweat

147 Copper Coupling, 1" sweat x 1" sweat fittings

Adapters, Male - Copper



116 Male Adapter, 3/4" sweat x 3/4" MIP fittings

120 Male Adapter, 1" sweat x 1" MPT fittings

0020-226 Coupling, 3/4" MPT x 1" female sweat fitting

0020-227 Coupling, 1" MPT x 1" female sweat fitting

0020-233 Coupling, 1" male sweat x 1" FPT fitting

Adapters, Female - Copper



164 Female Adapter, 1" sweat x 3/4" FIP fittings

117 Female Adapter, 3/4" sweat x 3/4" FIP fittings


Tees, Copper



138 Tee, Copper Pipe, 1" x 1" x 1" sweat fittings

255 Tee, Copper, 3/4" sweat fitting

Tee, Reducing - Copper



178 Reducing Tee, 1-1/2" x 1" x 1" sweat fittings

0020-231 Copper Tee, 2" x 1" x 1"

Solder & Soldering Flux



Low melting-point solder for easier soldering. Soldering flux includes brush. Use for easier soldering of copper sweat fittings.

1325 Solder

100 Soldering Flux (6 oz)

Brush, Cleaning



For cleaning the inside of copper fittings.

378 Cleaning Brush, 3/4"

379 Cleaning Brush, 1"

Crimp Kit, Fill Valve and Inline Strainer



Use 3/4" Black Pipe Plug (p/n 331) for clean-out port.

0020-325 Kit, Crimp - Fill Valve and Inline Strainer
0020-261 Inline Y-Strainer/Filter, 1" FPT

Crimp Kit, Forced Air Heat Exchanger



0020-327 Kit, Crimp - Forced Air Heat Exchanger

Crimp Kit, Brazed Plate to Boiler




0020-329 Kit, Crimp - Brazed Plate to Boiler

Crimp Kit, Brazed Plate to Domestic Water



0020-333 Kit, Crimp - Brazed Plate to Domestic Water

Crimp Fittings Adapter Kit, 25mm to 1"



2	A	Female Coupler, Brass, 3/4" FPT
4	B	PEX Male Adapter, 25mm x 3/4" MIP
4	C	PEX Clamp Crimp Ring, 25mm

PEX adapter kit for coupling 25mm ThermoPEX tubing to 1" Central PEX with crimp fittings. Crimp fittings included shown in illustration.

2500814 Crimp Fittings Adapter Kit, 25mm to 1" PEX

Sharkbite Kit, Existing Boiler, Plate Exchanger



2500706 Kit, Sharkbite - Existing Boiler, Plate Exchanger, for WoodMaster Traditional Models

Fittings Kit, Domestic Hot Water Plate Exchanger



Sharkbite Fittings Kit for installing a plate exchanger with 1" ports on an existing domestic hot water heater for thermal circulating heat transfer. Water-to-water plate exchanger is sold separately.


Each kit includes:

- 2 - Street Elbow, 90° Brass, 1"
- 2 - Sharkbite Female Adapter, 1" FPT
- 2 - Sharkbite Elbow, 90°, 3/4"
- 2 - Sharkbite Reduce Adapter, 3/4" x 1" FNPT

2500780 Sharkbite Fittings Kit - Plate Exchanger

Fittings - Kits


Fittings Kit, Single Pump Sharkbite®



Kit for installing a single pump in the pump panel area of CleanFire models. Circulating pump sold separately.

2500708 Single Pump Sharkbite Fittings Kit


Fittings Kit, Single Pump Crimp



Kit for installing a single pump in the pump panel area of CleanFire models. Circulating pump sold separately.

2500709 Single Pump Crimp Fittings Kit

Fittings Kit, Forced Air Furnace Heat Exchanger



Kit for installing a single pump on Traditional models and connecting to forced-air heat exchanger in furnace plenum. Circulating pump and heat exchanger sold separately.

2500705 Forced Air Heat Exchanger Fittings Kit

Sharkbite Fittings Kits with Single Pump and Heat Exchanger - CleanFire Models



Sharkbite Fittings Kit for CleanFire 300, 500, 700, 900 models. Circulating pump and heat exchanger are included. Use with a forced-air furnace system setup.

Each kit includes:

- 1 - Circulator Pump (pump can vary from image)
- 1 - Heat Exchanger Coil (see kit description for size)
- 8 - Sharkbite Reducer, 1" x 3/4" MNPT
- 2 - Sharkbite Ball Valve, 1"
- 1 - Pump Flange Kit, 3/4" FIP
- 1 - Swing Check Valve, 3/4" FIP
- 3 - Street Elbow, 90° Brass, 3/4"

Dimensions of heat exchanger coils included in the fittings kits:

- 80k Btu - 12-3/4" x 18" x 4-1/8"
- 95k Btu - 15" x 20" x 4-1/8"
- 125k Btu - 17-3/4" x 20" x 4-1/8"
- 140k Btu - 19" x 21" x 4-1/8"

- 2500748 Sharkbite Fittings Kit w/80k Btu Heat Exchanger Coil - CleanFire Models
- 2500749 Sharkbite Fittings Kit w/95k Btu Heat Exchanger Coil - CleanFire Models
- 2500750 Sharkbite Fittings Kit w/125k Btu Heat Exchanger Coil - CleanFire Models
- 2500751 Sharkbite Fittings Kit w/140k Btu Heat Exchanger Coil - CleanFire Models

Crimp Fittings Kits with Single Pump and Heat Exchanger - CleanFire Models



Crimp Fittings Kit for CleanFire 300, 500, 700, 900 models. Circulating pump and heat exchanger are included. Use with a forced-air furnace system setup.

Each kit includes:

- 1 - Circulator Pump (pump can vary from image)
- 1 - Heat Exchanger Coil (see kit description for size)
- 8 - Male Adapter, 1" PEX x 3/4" MIP
- 2 - Ball Valve, 1" PEX
- 1 - Pump Flange Kit, 3/4" FIP
- 1 - Swing Check Valve, 3/4" FIP
- 12 - PEX Clamp Crimp Ring, 1"
- 1 - Adapter Elbow, 90°, 1" PEX x 3/4" MPT
- 2 - Street Elbow, 90° Brass, 3/4"
- 1 - Cinch Tool

Dimensions of heat exchanger coils included in the fittings kits:

- 80k Btu - 12-3/4" x 18" x 4-1/8"
- 95k Btu - 15" x 20" x 4-1/8"
- 125k Btu - 17-3/4" x 20" x 4-1/8"
- 140k Btu - 19" x 21" x 4-1/8"

- | | |
|---------|--|
| 2500752 | Crimp Fittings Kit w/80k Btu Heat Exchanger Coil - CleanFire Models |
| 2500753 | Crimp Fittings Kit w/95k Btu Heat Exchanger Coil - CleanFire Models |
| 2500754 | Crimp Fittings Kit w/125k Btu Heat Exchanger Coil - CleanFire Models |
| 2500755 | Crimp Fittings Kit w/140k Btu Heat Exchanger Coil - CleanFire Models |

Sharkbite Fittings Kits with Single Pump and Heat Exchanger - Traditional Models



Sharkbite Fittings Kit for Traditional 3300, 4400, 5500, 6500 models. Circulating pump and heat exchanger are included. Use with a forced-air furnace system setup.

Each kit includes:

- 1 - Circulator Pump (pump can vary from image)
- 1 - Heat Exchanger Coil (see kit description for size)
- 1 - 2" Black Nipple, 1" NPT
- 2 - Sharkbite Male Adapter, 1" MPT
- 2 - Street Elbow, 90° Brass, 3/4"
- 1 - Pump Flange Kit, 1" FIP
- 2 - Push-fit Reducer, 1" x 3/4" MPT

Dimensions of heat exchanger coils included in the fittings kits:

- 80k Btu - 12-3/4" x 18" x 4-1/8"
- 95k Btu - 15" x 20" x 4-1/8"
- 125k Btu - 17-3/4" x 20" x 4-1/8"
- 140k Btu - 19" x 21" x 4-1/8"

- | | |
|---------|--|
| 2500756 | Sharkbite Fittings Kit w/80k Btu Heat Exchanger Coil - Traditional Models |
| 2500757 | Sharkbite Fittings Kit w/95k Btu Heat Exchanger Coil - Traditional Models |
| 2500758 | Sharkbite Fittings Kit w/125k Btu Heat Exchanger Coil - Traditional Models |
| 2500759 | Sharkbite Fittings Kit w/140k Btu Heat Exchanger Coil - Traditional Models |

Fittings - Kits

Crimp Fittings Kits with Single Pump and Heat Exchanger - Traditional Models



Crimp Fittings Kit for Traditional 3300, 4400, 5500, 6500 models. Circulating pump and heat exchanger are included. Use with a forced-air furnace system setup.

Each kit includes:

- 1 - Circulator Pump (pump can vary from image)
- 1 - Heat Exchanger Coil (see kit description for size)
- 1 - 2" Black Nipple, 1" NPT
- 2 - PEX Male Adapter, 1" PEX x 1" MPT
- 1 - Pump Flange Kit, 1" FIP
- 4 - PEX Clamp Crimp Ring, 1"
- 2 - Male Adapter, 1" PEX x 3/4" MIP
- 2 - Street Elbow, 90° Brass, 3/4"
- 1 - Cinch Tool

Dimensions of heat exchanger coils included in the fittings kits:

- 80k Btu - 12-3/4" x 18" x 4-1/8"
- 95k Btu - 15" x 20" x 4-1/8"
- 125k Btu - 17-3/4" x 20" x 4-1/8"
- 140k Btu - 19" x 21" x 4-1/8"

- 2500760 Crimp Fittings Kit w/80k Btu Heat Exchanger Coil - Traditional Models
- 2500761 Crimp Fittings Kit w/95k Btu Heat Exchanger Coil - Traditional Models
- 2500762 Crimp Fittings Kit w/125k Btu Heat Exchanger Coil - Traditional Models
- 2500763 Crimp Fittings Kit w/140k Btu Heat Exchanger Coil - Traditional Models

Sharkbite Fittings Kits with Single Pump and Heat Exchanger - Maxim M255 PE Models



Sharkbite Fittings Kit for Maxim M255 PE models. Circulating pump and heat exchanger are included. Use with a forced-air furnace system setup.

Each kit includes:

- 1 - Circulator Pump (pump can vary from image)
- 1 - Heat Exchanger Coil (see kit description for size)
- 2 - Sharkbite Elbow, 90°, 1"
- 2 - Nipple, Black, 3/4"
- 1 - Pump Flange Kit, 3/4" FIP
- 2 - Ball Valve, Brass, 3/4" FIP
- 1 - Check Valve, Swing, Brass, 3/4" FIP
- 4 - Sharkbite Reducer, 1" x 3/4" MPT
- 2 - Street Elbow, 90° Brass, 3/4"

Dimensions of heat exchanger coils included in the fittings kits:

- 80k Btu - 12-3/4" x 18" x 4-1/8"
- 95k Btu - 15" x 20" x 4-1/8"
- 125k Btu - 17-3/4" x 20" x 4-1/8"
- 140k Btu - 19" x 21" x 4-1/8"

- 2500764 Sharkbite Fittings Kit w/80k Btu Heat Exchanger Coil - M255 PE
- 2500765 Sharkbite Fittings Kit w/95k Btu Heat Exchanger Coil - M255 PE
- 2500766 Sharkbite Fittings Kit w/125k Btu Heat Exchanger Coil - M255 PE
- 2500767 Sharkbite Fittings Kit w/140k Btu Heat Exchanger Coil - M255 PE

Crimp Fittings Kits with Single Pump and Heat Exchanger - Maxim M255 PE Models



Crimp Fittings Kit for Maxim M255 PE models. Circulating pump and heat exchanger are included. Use with a forced-air furnace system setup.

Each kit includes:

- 1 - Circulator Pump (pump can vary from image)
- 1 - Heat Exchanger Coil (see kit description for size)
- 2 - PEX Elbow, 90° Brass, 1"
- 2 - Nipple, Black, 3/4"
- 1 - Pump Flange Kit, 3/4" FIP
- 2 - Ball Valve, Brass, 3/4" FIP
- 1 - Check Valve, Swing, Brass, 3/4" FIP
- 4 - PEX Male Adapter, 1" PEX x 3/4" MIP
- 8 - PEX Clamp Crimp Rings, 1"
- 2 - Street Elbow, 90° Brass, 3/4"
- 1 - Cinch Tool

Dimensions of heat exchanger coils included in the fittings kits:

- 80k Btu - 12-3/4" x 18" x 4-1/8"
- 95k Btu - 15" x 20" x 4-1/8"
- 125k Btu - 17-3/4" x 20" x 4-1/8"
- 140k Btu - 19" x 21" x 4-1/8"

- 2500768 Crimp Fittings Kit w/80k Btu Heat Exchanger Coil - M255 PE
- 2500769 Crimp Fittings Kit w/95k Btu Heat Exchanger Coil - M255 PE
- 2500770 Crimp Fittings Kit w/125k Btu Heat Exchanger Coil - M255 PE
- 2500771 Crimp Fittings Kit w/140k Btu Heat Exchanger Coil - M255 PE

Sharkbite Fittings Kits with 30-Plate Heat Exchanger



Sharkbite Fittings Kit for installing a 4.57" x 11.26" plate exchanger with 1" ports on an existing domestic hot water heater for thermal circulating heat transfer. Water-to-water 30-plate, 100k Btu exchanger is included.

Each kit includes:

- 1 - Heat Exchanger, 30-Plate, 100k Btu
- 2 - Street Elbow, 90° Brass, 1"
- 2 - Sharkbite Female Adapter, 1" FPT
- 2 - Sharkbite Elbow, 90°, 3/4"
- 2 - Sharkbite Reduce Adapter, 3/4" x 1" FNPT

- 2500744 30-Plate Exchanger w/Sharkbite Fittings

Aquatstats / Thermostats

Aquatstats & Thermostats

0020-376




0020-377



0020-376 Electronic Aquastat with 8' wire and 1/4" probe

0020-377 Strap-On Aquastat (2E859)


Aquastat, Immersible - Adjustable



Adjustable between 110-240°F, immersible, with 1/2" MPT fittings on well (either close on rise or open on rise). Well is included with aquastat. Recommended operating setting is between 165-195°F.

169 Adjustable Aquastat with Well, 1/2" MPT

Fan Center Relay



The Fan Center Relay is used to control a 110-volt fan with a 24-volt thermostat.

515 Fan Center Relay

0020-380




0020-382



0020-380 Low-Volt Thermostat, 24V

0020-382 Circuit Transformer

Thermostat, Line Voltage



Line Voltage Thermostat (120-volt) used to start the fan on forced-air systems.

1267 Line Voltage Thermostat

Relay, 24-Volt



Used to connect a 24-volt thermostat to existing thermostat for a heat pump.

8200293 Power Relay, 24V, SPNO-SPNC


Relay, 24-Volt



Fan relay used to control fan or other circuits with 24VAC.

0020-383 Fan Relay, 24V


Thermostat, Plug-in



Plug-in Thermostat, 13.5-amp rated, 110-Volt, is for operating fan.

368 Plug-in Thermostat


Transformer, 24-Volt



Used with 24-volt wall thermostat and 24-volt zone valves.

188 24-Volt Transformer

Vent Valve, Automatic



Vents air automatically. For use in pressurized systems only. Fitting is 1/8" NPT.

286 Automatic Vent Valve

Check Valves



0020-403

0020-403 Brass Swing Check Valve, 1" FPT

Check Valve, Swing - Brass



Brass Swing Check Valve with FIP fittings prevents reverse circulation.

296 Brass Swing Check Valve, 3/4"
5871 Brass Swing Check Valve, 1-1/4"

Tempering Valve, Sweat



Tempering Valve has temperature range of 110°F - 170°F.


0020-408 Tempering Valve, 3/4" Sweat

Radiant Mixing Valve, Sweat



0020-410 Radiant Mixing Valve, 1" Sweat
0020-411 Radiant Mixing Valve, 3/4" Sweat

Zone Valves, Zone Sentry®



On-off, normally open or normally closed control in open and closed hydronic systems. Simple to install and operate, the valve can be installed in any direction, in any orientation. Snap-in quick connects make for a simple and secure wiring hook-up. LED shows full functionality of the valve's operation and thermostat status. Uses half the power of the 560 Series Zone Valves. 2-way or 3-way zone valves available.

5800059 3-Way Zone Sentry Zone Valve, 1" NPT threads
5800021 3-Way Zone Sentry Zone Valve, 3/4" NPT threads
5800030 3-Way Zone Sentry Zone Valve, 3/4" sweat
5800028 3-Way Zone Sentry Zone Valve, 1" sweat
5800020 2-Way Zone Sentry Zone Valve, 3/4" NPT threads
5800027 2-Way Zone Sentry Zone Valve, 1" sweat
5800022 Replacement Actuator Head for Zone Sentry Valve

Caleffi 2-Way Zone Valve, 3/4" FNPT



Two-way on/off two position valve, straight-through flow pattern, brass body, stainless steel stem, EPDM rubber seals and paddle. 3/4" FNPT connections. Requires Switch, sold separately.

5800043 Zone Valve, 2-Way, 3/4" FNPT

Caleffi 2-Way Zone Valve, 1" Sweat



Two-way on/off two position valve, straight-through flow pattern, brass body, stainless steel stem, EPDM rubber seals and paddle. 1" sweat connections. Requires Switch, sold separately.

5800044 Zone Valve, 2-Way, 1" Sweat

Caleffi 3-Way Zone Valve, FNPT



Three-way on/off two position valve, diverting flow pattern, brass body, stainless steel stem, EPDM rubber seals and paddle. 3/4" or 1" FNPT connections. Requires Switch, sold separately.

5800045 Zone Valve, 3-Way, 3/4" FNPT
5800060 Zone Valve, 3-Way, 1" NPT

Valves

Caleffi 3-Way Zone Valve, Sweat




Three-way on/off two position valve, diverting flow pattern, brass body, stainless steel stem, EPDM rubber seals and paddle. 3/4" or 1" sweat connections. Requires Switch, sold separately.

5800046 Zone Valve, 3-Way, 3/4" Sweat

5800047 Zone Valve, 3-Way, 1" Sweat

Caleffi Zone Valve Switches



Shown Installed

Z1 actuator for motorized zone valves (closed). Easy push-button attachment, 7/8" knockout for 1/2" conduit connector. With auxiliary microswitch.

Rating of auxiliary switch contacts:


5800058 – 0.0 A min, 0.4 A max (24 V to 120 V)

5800049 – 0.25 A min, 5.0 A max (230 V).

5800049 Switch, Zone Valve, 24V, 5A, NC, 18" Wires

5800058 Switch, Zone Valve, 24V, 0.4A, NC, Terminal Block


Caleffi 3-Way Thermostatic Mixing Valve, 3/4" NPT



Adjustable thermostatic mixing valve for point of distribution in domestic water systems and radiant hydronic heating systems. Low-lead brass body. Locking set point knob.

5800052 3-Way Thermostatic Mixing Valve, 3/4" NPT


Caleffi TankMixer, 3/4" NPT



Thermostatic mixing valve kit for domestic water heaters. Adjustment temperature range: 95°F - 150°F. 3/4" MPT fittings.

5800048 TankMixer, 3/4" NPT


DISCAL® Air Separator



Brass body. Stainless steel float guide pin and linkage. Glass reinforced nylon internal element. 1" NPT female bottom thread. Air separation efficiency: up to 100% removal.

5800051 DISCAL Air Separator, 1" FNPT

Ball Valve, Sweat



200

Sweat Ball Valve, 3/4" x 3/4" sweat fitting - Lead Free

Ball Valve, PEX




Full port ball valve for Central PEX.

5000556 Ball Valve, 1/2" PEX, Full Port

5000557 Ball Valve, 1" PEX, Full Port

Ball Valve



Brass FIP Ball Valves. The 3/4" Full Port Ball Valve (p/n 198) is used on both sides of the pump and on the furnace for each water line.

186 Ball Valve, 1/2"

198 Ball Valve, 3/4" Full Port - Lead Free

Hose Bibs, Brass



Brass hose bib, 3/4" MPT. Use brass cap (p/n 5348) with washer (p/n 5349) to cover end.

199

Brass Hose Bib, 3/4" MPT

5349

Washer, 3/4"

5348

Cap, Brass, 3/4"


Valve, Tempering



Mixing valve for tempering hot water, with an adjustable temperature range between 120-160°F.

140 Tempering Valve, 3/4" sweat fittings


Valve, Radiant Mixing



For controlling water temperature in various types of radiant heat systems. Temperature range 70°F - 145°F. Not an anti-scald valve and not intended to be used on water heaters.

306 Radiant Mixing Valve, 1/2" NPT fittings
 327 Radiant Mixing Valve, 3/4" NPT fittings
 329 Radiant Mixing Valve, 1" NPT fittings

Valve, Water Heater Mixing



Designed specifically for water heaters, with a temperature range of 90°F - 130°F. Includes 18" braided hose and brass tee.

5000392 Water Heater Mixing Valve, 3/4" NPT fittings,
 lead free

Chimney

Chimneys - Traditional Models

NOTE: For Traditional furnaces manufactured after January 2023 with serial # noted or before August 11, 2009.

WM 3300SS - first serial # WT30139 and up

WM 4400SS - first serial # WT40306 and up

6500004	6" x 48" Chimney
6500038	6" x 24" Chimney
6500036	6" Chimney Coupler
2900595	6" Chimney Rain Cap

WM 5500SS - first serial # WT50175 and up

10508	8" x 48" Chimney
6500039	8" x 18" Chimney
6500037	8" Chimney Coupler
10774	8" Chimney Rain Cap

SuperPro Chimneys (Selkirk)

NOTE: SuperPro Chimneys fit furnaces manufactured after August 11, 2009 until January 2023 (see note above).

SuperPro Chimneys - 6" Diameter

1709-060	6" Chimney Cap
1709-061	6" Cover Cap
1709-062	6" Chimney Male Coupler
1709-063	Chimney Spark Arrestor Mesh, 6"
1709-064	6" x 24" SuperPro SS Chimney
1709-065	6" x 48" SuperPro SS Chimney
1709-069	6" Chimney Locking Band

SuperPro Chimneys - 8" Diameter

1709-080	8" Chimney Cap
1709-082	8" Male Coupler
1709-083	Chimney Spark Arrestor Mesh, 8"
6500035	8" x 18" SuperPro SS Chimney
1709-084	8" x 24" SuperPro SS Chimney
1709-085	8" x 48" SuperPro SS Chimney
1709-089	8" Chimney Locking Band

Chimney Coupler

6500037	8" Stainless Steel Chimney Coupler
6500036	6" Stainless Steel Chimney Coupler


Chimney Band Clamp Kit, 8"



Reinforces strength between two sections of 8" chimney.

4518	Chimney Band Clamp Kit, 8"
------	----------------------------


Chimney Base Brace Kit, 6"



Used to reinforce the chimney base when three or more chimney sections are used.

2500044	Chimney Base Brace Kit, 6"
---------	----------------------------

Chimney Base Brace Kit, 8"



Used to reinforce the chimney base when three or more chimney sections are used.

4519	Chimney Base Brace Kit, 8"
------	----------------------------

Clamp, Snaplock Chimney - 8"

10509	Clamp, Snaplock Chimney - 8"
-------	------------------------------


Chimney Guy-Wire Band Kit, 8"



Used to provide additional stability to chimneys in installations where property damage could occur within the fall zone of the chimney. Guy wire is not included in kit.

778	Chimney Guy-Wire Band Kit
-----	---------------------------

Chimney Cap/Spark Arrestor



New version chimney cap/spark arrestor provides better fit, features a snaplock clamp and screen that is secured with a clamp-on fastener for easy removal. Available for 6" and 8" chimneys. Compatible with Security chimneys.

2900597	6" Chimney Cap/Spark Arrestor
2900598	8" Chimney Cap/Spark Arrestor

Twist-Lock Chimneys (Security)


NOTE: Twist-Lock Chimneys fit furnaces manufactured before August 11, 2009.

6500004	6" x 48" Twist-Lock Stainless Steel Chimney
10508	8" x 48" Twist-Lock Stainless Steel Chimney
0709-100	10" Twist-Lock Chimney Cap
0709-102	10" Twist-Lock Male Coupler
0709-104	10" x 24" Twist-Lock Stainless Steel Chimney
0709-105	10" x 48" Twist-Lock Stainless Steel Chimney
0709-130	Twist-Lock Spark Arrestor Mesh

Draft Inducer Kits

0109-734	Draft Inducer, LT 90 and AFS models
----------	-------------------------------------


Chimney Sections, 6" - Maxim



Type HT listed, factory-built, all stainless steel 6" chimney section. Sections are four feet long. Chimney Snaplock Clamp (6500011) should be used at each joint.

6500004	6" x 48" Chimney Extension
6500011	6" Chimney Snaplock Clamp


Chimney Band Clamp Kit, 6"



Reinforces strength between two sections of 6" chimney.

9535	Chimney Band Clamp Kit, 6"
------	----------------------------

Chimney Guy-Wire Band, 6"



Attached to the outer casing of a 6" chimney to hold three guy-wires (not included). Recommended for chimneys exceeding the roof by 5' to 13' maximum.

776	Guy-Wire Band
-----	---------------

Corrosion Inhibitor, Treatment

MolyArmor 350 Corrosion Inhibitor



MolyArmor 350 Corrosion Inhibitor (boiler treatment) provides excellent water jacket corrosion protection when properly maintained at a minimum of 350 ppm. It is easy to test for maintenance levels with a test kit (p/n 2500691). One gallon of MolyArmor 350 Corrosion Inhibitor treats 200 gallons of system water.

Models	Initial MolyArmor 350 Amount
Maxim M255 PE; 3300	1/2 gal.
CleanFire 300, 500; 4400, 5500	1 gal.
CleanFire 700	2 gal.
CleanFire 900	3 gal.
6500	2-1/2 gal.
2900631	MolyArmor 350 Corrosion Inhibitor, 1 gal.

Moly/pH Single Strip Test Kit




Test Kit for testing your furnace water when treated with MolyArmor 350 Corrosion Inhibitor. Test kit is a vial of 25 strips that only requires a single test strip for testing both pH and Moly. Instructions are provided on the label of the kit bottle.

Note that timing is important when checking the test pad to the color chart.

2500691 Moly/pH Single Strip Test Kit

Water Sample Bottle Kit



Used to submit required water samples for CleanFire model furnaces. Each kit includes two bottles, two shipping boxes, and two generic mailing labels. Includes instructions.

2500686 Kit, Water Sample Bottle

Sludge Conditioner



Reduces mineral deposits in boiler side of water-to-water heat exchangers. Can be used as a preventative when filling the furnace or as a rescue treatment if corrosion occurs in the water jacket due to improperly maintained Corrosion Inhibitor levels.

Refer to following chart for the amount to use for each model furnace for preventative or rescue treatment applications. Note that 1 unit = 1 gallon.

PREVENTATIVE IN HARD WATER: While it is best to use softened water when filling the furnace, Sludge Conditioner should be used if the water quality is known to contain higher concentrations of minerals or solids.

RESCUE TREATMENT FOR CORROSION: If a furnace has been subjected to low Corrosion Inhibitor levels and corrosion is evident in the water jacket, Sludge Conditioner can be used by circulating through the furnace for one week to help clean some of the corrosion from inside the water jacket before flushing and refilling.

Models	Preventative Amount	Rescue Amount
Maxim M255 PE; 3300, 4400		
CleanFire 300	1/2 unit	1 units
CleanFire 500, 700; 5500	1 unit	2 units
CleanFire 900; 6500	2 units	4 units
166	Sludge Conditioner, 1 gal.	

CS-25 Alkalinity Builder



CS-25 Alkalinity Builder is an additive for increasing the alkalinity (pH) of systems that have been treated with propylene glycol antifreeze if MolyArmor 350 has achieved 350+ ppm moly but the pH of the treated system water is lower than 8.0.

To use, add 32 ounces of CS-25 Alkalinity Builder, circulate at operating temperature for 48 hours and test pH again. Repeat as needed, adding 32 ounces at a time and circulating for 48 hours before testing again.

If the system was NOT treated with propylene glycol antifreeze, MolyArmor 350 was added to achieve 350+ ppm moly, and the pH is lower than 8.0, drain the system. Then use makeup water from an alternate source that is within the recommended level of 6.5 - 8.0 pH before being treated with MolyArmor 350.

2900667 CS-25 Alkalinity Builder, 1-gallon

Replacement Fan

- 0109-730 Replacement Fan (4C012) - 328, old 434
 0109-731 Replacement Fan (4C004) - 3300, 434, 5500 (rear), AFS 900 and LT90



0109-732

- 0109-732 Replacement Fan (4C446) - 4400, 5500, 546, 6500, 658 & AFS1100
 5800040 Replacement Fan - 4400, 5500, 546, 6500, 658 & AFS1100



0109-790

- 0109-790 Solenoid, Laminated
 6145 Draft Spring

Replacement Fan Cover



0709-051

- 0709-051 Fan Cover, WoodMaster Models and LT 90
 0109-101 Snap Disc, Auto Reset, 190°F/150°F Traditional Models



0109-103

- 0109-103 Snap Disc, Manual Reset, 180°F, MF5500, AFS 900

Firebox Door



3300 Firebox Door

- 2700282 Firebox Door, 3300/434
 2700283 Firebox Door, 4400/546
 2700284 Firebox Door, 5500
 2001242-011 Firebox Door, 6500, LH
 2001243-011 Firebox Door, 6500, RH
 7992-110 Firebox Door Assembly, AFS900/1100/LT90
 0409-012 Firebox Door Handle Knob, 3300, 4400, 5500, 6500

Replacement Silicone



- 806 Black Silicone Adhesive, High Temperature, 10.1 oz

Furnace Replacement Parts

Replacement Door Rope



- 7594 Door Rope, 1" Fiberglass, Firebox - Per Foot (250' per box)

ETC Assembly, Wood Stove



- 7992-901 ETC Panel Assembly, Wood Stove
 0109-154 Circuit Breaker Switch, 10A

Dixell Temp Control



- 0109-001 Dixell Temp Control
 0409-027 ETC Gasket
 0109-152 Fan Switch, ON/OFF
 0409-003 ETC Back Box
 430-0021 ETC Cover UV Shield
 0219-021 Lock Nut, Center, 5/16"-18 (requires 4 per panel)

Replacement Harnesses

- 0109-401 ETC Wire Harness, Wood Stoves
 0109-411 Stove Harness, Single Blower - 3300/4400
 0109-412 Stove Harness, Double Blower - 5500
 0109-413 Stove Harness - 6500

Replacement Night Light Glass Cover



0020-777

- 0020-777 Glass Cover, Night Light

Replacement Stove Light w/Glass Cover

- 0109-241 Stove Light w/Glass Cover

Replacement Water Level Light



0109-245

- 0109-245 Water Level Light Receptacle, Green LED



0109-100

- 0109-100 Float Assembly for Water Level Light



0109-153

- 0109-153 Switch, Light On/Off

Furnace Replacement Parts

Replacement Thermistor



The Thermistor w/Brass Probe (p/n 726) can be used in CleanFire models and can replace 0109-002 in WoodMaster Traditional furnaces.

0109-002 Thermistor, Digital Aquastat
726 Thermistor w/Brass Probe

Replacement Thermowell



0109-003 Thermowell, 1/2"

Replacement Temperature Probe

0109-620 Temperature Probe, LT 90 RTD

Replacement Water Pressure Switch




0109-192 Water Pressure Switch, 1-1/4"

Replacement On/Off Switch

0109-152 Switch, Fan On/Off

Slide Rod Plates

Slide Rod Plate



1200908 Slide Rod Plate, 3300
1200903 Slide Rod Plate, 4400
1200910 Slide Rod Plate, 5500
1200913 Slide Rod Plate, 6500

Slide Rod/Assemblies


7992-033 Breakaway Slide Rod Assembly, 3300



4400 Breakaway
Slide Rod

7992-044 Breakaway Slide Rod Assembly, 4400
7992-055 Breakaway Slide Rod Assembly, 5500
7992-065 Slide Rod Assembly, 6500
7992-332 Slide Rod/Slide Plate Kit, 3300
7992-442 Slide Rod/Slide Plate Kit, 4400
7992-552 Slide Rod/Slide Plate Kit, 5500
7992-652 Slide Rod/Slide Plate Kit, 6500

Over Fire Air Tube



0909-561 Air Tube, Over Air, 5500

Ash Removal Systems

Ash/Auger Kit



7992-444 Ash/Auger Kit, 4400
0809-400 Ash Grate, 4400
0809-404 Triple Auger Assembly, 4400
0809-403 Triple Ash Auger WMT,
Inside (Center Auger), 4400
7992-554 Ash/Auger Kit, 5500
0809-500 Ash Grate, 5500
0809-504 Triple Auger Assembly, 5500
0809-503 Triple Ash Auger WMT,
Inside (Center Auger), 5500
2001236 Auger Tube Cover w/Ash Drop Out Door
0909-401 Crank Handle, Ash Auger (fits all models)

Auger Chains



0020-800 Auger Chain, 4400
0020-801 Auger Chain, 5500

Replacement Vent Cap

7992-021



7992-021 Vent Cap

AFS Replacement Parts

AFS Replacement Parts - Fire Pot



0809-012

0809-012 Fire Pot, AFS 900

7995-013 Fire Pot With End Plate, AFS 1100



0611-022

0611-022 Front Plate, AFS 1100

AFS Replacement Parts - Augers



0609-500

0609-500 High Temperature Auger, AFS 900

AFS Replacement Parts - Motor Items



0109-701

0109-701 Motor, AFS 900



0109-702

0109-702 Motor, AFS 1100

AFS Replacement Parts



0109-194

0109-194 Air Pressure Switch, AFS 900



0109-601

0109-601 Ignitor, AFS 900 (800 Watt)



0209-252

0209-252 Morris Coupling

0209-254 Morris Coupling Gasket Seal

Flex Fuel Replacement Parts

Flex Fuel Replacement Parts - Handles

0409-013 Firebox Handle

Flex Fuel Replacement Parts - Heat Exchanger Gaskets



Heat Exchanger
Gasket

6000057 Heat Exchanger Gasket, 30 kW

041-0006 Heat Exchanger Gasket, 60 kW

Flex Fuel Replacement Parts - Grates




Pellet Grate
Insert

351-7000 Pellet Grate Insert, 30 kW

Flex Fuel Replacement Parts - Control Panel Displays

011-0013 30 kW Control Panel Display

011-0016 60 kW Control Panel Display



011-0006

Flex Fuel Replacement Parts - I/O Board

011-0006 I/O Board

Renovator Replacement Parts

Renovator Replacement Parts - Air Box Gasket Rope Kit

420-0008 Kit, Renovator Air Box Gasket Rope

Renovator Replacement Parts - Burn Pot



Renovator 20
Burn Pot

- 800-0116 Burn Pot, Renovator 20
- 800-0133 Burn Pot, Renovator 30
- 610-0367 Flame Guard

Renovator Replacement Electronics



100-0035

- 100-0035 Snap Disc, Renovator 20
- 100-0048 Relay, Renovator
- 100-0043 Temperature Control, Renovator
- 160-0000 Ignitor, 400W
- 100-0037 Photosensor

Renovator Replacement Parts - Combustion Fan



430-0009

- 430-0009 Hose, Blue Intake, 22"
- 120-0003 Combustion Fan, Renovator

Options and Tools

Sediment Trapper Filter, Hot Water, 3/4"



Centrifugal separation technology and 100 mesh filter element. Amber see-through cover easily removable for cleaning using no tools. Bottom valve used to empty sediment. Stainless steel screen filter is cleanable and reusable.

Rated to 200°F (93°C) @ 40 psi. Dimensions: 14-3/8"L x 5"W. Port size: 3/4" FPT.

- 2900578 Hot Water Sediment Trapper Filter, 3/4" FPT
5000683 O-Ring, Replacement, for Hot Water Filter (p/n 2900578)


Multimeter, Digital Pocket



Digital multimeter performs several electrical measurement functions in one simple-to-use instrument.

- 2657 Digital Pocket Multimeter

Hoe, Firebox



Used as a firebox maintenance tool; hoe includes metal handle.


- 2900001 Hoe, Firebox, 72"

Hoe, Ash

For use in all wood stoves.

- 7992-329 Ash Hoe

Ash Shovel, Reaction Chamber




Flat shovel is used to remove ash. The shovel head angle allows for cleaning to the back of the Reaction Chamber on CleanFire models.

- 2900535 Ash Shovel

Brush, Stainless Steel

- 0020-772 Stainless Steel Brush, 2" x 36" for tube cleaning


Torch, Outdoor



Torch design allows easy starting of the fire in CleanFire and Maxim models.

- 2900325 Outdoor Torch


24V Fan Conversion Kit



Kit is used to allow a CleanFire furnace to be operated with 24V DC (for systems off the grid, for example). Includes a 24V Combustion Fan and a low-voltage replacement power supply. Only for CleanFire 300, 500 or 700 (will not work for CleanFire 900).

- 2500633 24V Fan Conversion Kit


Pump Panel Extension Kit - CleanFire 300/500



Kit provides additional room for mounting more than one pump on CleanFire 300 or 500 models.

- 2500164 Pump Panel Extension Kit


Chimney Cleaning Kit - 6"



Kit for cleaning both the horizontal and vertical portions of all 6" chimneys. Includes components shown above. Replacement components may be purchased individually.

- 2500738 Chimney Cleaning Kit, 6"
2900485 6" Chimney Brush
312 Extension Rod, 48" Fiber
2900488 Extension Rod, 48" Wire
2900490 Handle


Chimney Cleaning Kit - 8"



Kit for cleaning both the horizontal and vertical portions of all 8" chimneys. Includes components shown above. Replacement components may be purchased individually.

- 2500739 Chimney Cleaning Kit, 8"
2900486 8" Chimney Brush
312 Extension Rod, 48" Fiber
2900488 Extension Rod, 48" Wire
2900490 Handle


Door Seal



Kits include silicone-coated fiberglass door seal, Black Silicone and instructions.

- 2500697 Door Seal Kit - CleanFire 300, 500
- 2500698 Door Seal Kit - CleanFire 700, 900
- 4050036 Foam Bumper Pad, Door Switch - CleanFire models 806
- Black Silicone, 10 oz.


Rope, Door Seal



Sold either by the foot or in pre-cut lengths for specific model applications (282' per box). Silicone is not included.

- 7674 Rope, 7/8", priced per ft


Door Seal, Silicone-Coated, 100-ft



Silicone-coated 7/8" Door Seal is available in 100-foot lengths. Minimum lengths for CleanFire models: 300=71", 500=79", 700=99", 900=106".

- 6000064 Door Seal, Silicone-Coated, 7/8", 100-ft


Chimney Sections, 8" - CleanFire 700/900



8" Stainless steel chimney currently shipped with CleanFire 700 models. Compatible with Chimney Extension (p/n 6500002). If connecting to Chimney Extension (p/n 6500002), use 8" Chimney Band Clamp Kit (p/n 4518) at the joints, not Chimney Snaplock Clamp (p/n 10509). For outdoor applications only. Not to be used for venting of indoor heating appliances.

- 10508 8" Chimney Extension, 4'
- 10509 Chimney Snaplock Clamp, 8"


Chimney Sections, 6" - CleanFire 300 and 500



Type HT listed, factory-built, all stainless steel 6" chimney section. Sections are four feet long. Chimney Snaplock Clamp (6500011) should be used at each joint.

- 6500004 6" Chimney Extension, 4'
- 6500011 Chimney Snaplock Clamp, 6"

Chimney Cap/Spark Arrestor



New version chimney cap/spark arrestor provides better fit, features a snaplock clamp and screen that is secured with a clamp-on fastener for easy removal. Available for 6" and 8" chimneys.

- 2900597 6" Chimney Cap, Spark Arrestor
- 2900598 8" Chimney Cap, Spark Arrestor

Chimney Band Clamp Kit, 6"



Reinforces strength between two sections of 6" chimney.

- 9535 Chimney Band Clamp Kit, 6"


Chimney Band Clamp Kit, 8"



Reinforces strength between two sections of 8" chimney.

- 4518 Chimney Band Clamp Kit, 8"

Chimney Attachment Ring



Used with electrical conduit (not included) to reinforce chimney when five or more sections are used. For 6" chimneys, must be located directly below 6" Chimney Locking Band (p/n 6500011) to reduce stress on the joint. For 8" chimneys, must be located directly below 8" Chimney Locking Band (p/n 10509) to reduce stress on the joint.

- 774 Chimney Attachment Ring

CleanFire Furnace Parts & Accessories

Chimney Guy-Wire Band, 6"



Attached to the outer casing of a 6" chimney to hold three guy-wires (not included). Recommended for chimneys exceeding the roof by 5' to 13' maximum.

776 Guy-Wire Band


Chimney Guy-Wire Band Kit, 8"



Used to provide additional stability to chimneys in installations where property damage could occur within the fall zone of the chimney. Guy wire is not included in kit.

778 Chimney Guy-Wire Band Kit

Chimney Tee Kits, Stainless Steel



Type HT listed, factory-built, all stainless steel chimney tee. Kit includes chimney tee cover and chimney tee rope rings. NOTE: Silicone (p/n 806) is not included.


8" Chimney Tee Kit (p/n 2500621) - CleanFire 700 and 900.

6" Chimney Tee Kit (p/n 2500620) - CleanFire 300 and 500.

2500621 8" Chimney Tee Kit

2500620 6" Chimney Tee Kit

Chimney Tee Covers



Replacement chimney tee cover.

10775 8" Cover - CleanFire 700 and 900

2900319 6" Cover - CleanFire 300 and 500

Chimney Rope Ring

Replacement rope ring for chimneys. See table below for applications. When ordering p/n 809, specify the length in feet.

Model	Rope Ring part number	
	Between chimney connector and furnace	Below first chimney section
CleanFire 700/900	6000033	7632
CleanFire 300/500	6000034	809 (order 2 ft)


6000033 Rope Ring (only), 2" Low Density Braid, 8" I.D.

6000034 Rope Ring (only), 1.75" Low Density Braid, 6" I.D.

7632 Rope Ring, 3/4", 8" ID

809 Door Seal Rope, 3/4", priced per ft
(394' per box)

Scraper Tool



Used to maintain and clean the firebox.

2900534 Scraper Tool

Cleaning Rod - CleanFire



Used to clean the firebox.

2001235 Cleaning Rod


Cleaning Tool, Heat Exchanger



Tool for cleaning CleanFire rear heat exchangers.

3105186-011 Heat Exchanger Cleaning Tool


Cleaning Tool, Afterburner



Tool for cleaning Afterburner and Reaction Chamber on CleanFire models.

1200897-011 Afterburner Cleaning Tool


Grounding Rod Kit



Used to electrically ground the furnace.

6593 Grounding Rod Kit

FireStar XP Outdoor Wi-Fi Module Kit



Outdoor Wi-Fi wireless display can be used to remotely view operational data on the FireStar II controller. Compatible only with a properly configured FireStar II equipped outdoor furnace (with software version 2.5x or higher on Maxim M255 PE models).

Kit includes FireStar XP Outdoor Wi-Fi Module, antenna, wiring, Quickstart Guide, Operator's Manual and installation instructions.

NOTE: Wireless range varies widely with each installation. Prior to purchase, a site survey (using a smartphone or laptop) should be performed to determine if the furnace site is within range of customer's existing Wi-Fi network. Range is generally up to 100 feet when unobstructed and there is no interference. Uses 802.11 technology.

2500185 FireStar XP Outdoor Wi-Fi Module Kit
8200080 Wi-Fi Antenna Only

Ash Scoop - Maxim



4-Quart galvanized Ash Scoop is ideal for cleaning ashes from furnace.

315 Ash Scoop

Flue Brush & Handle



Used to clean the flue passageways of M255 PE models. Flue Brush Kit (p/n 390) includes 398, 312 and handle. Not to be used for cleaning 6" or 8" chimney.

390 Flue Brush Kit
312 Extension Rod, 48"
398 Flue Brush
2900490 Replacement Handle

Cleaning Rod - Maxim




Used to clean the firebox.

317 Cleaning Rod

Maxim Furnace Parts & Accessories


Hopper, 48-Bushel Kit w/Auger - Maxim M255 PE



Increases fuel storage capacity, for Maxim M255 PE models. Includes 5-1/2' auxiliary auger to locate the 48-Bushel Hopper to the side of the outdoor furnace. Available in either green and olive gray or terra brown and taupe to match the Maxim. Dimensions: 48" x 48" x 66".

2500724-202 48-Bushel Hopper w/5-1/2' Auger Kit -
Green and Olive Gray
2500724-021 48-Bushel Hopper w/5-1/2' Auger Kit -
Terra Brown and Taupe

Auxiliary Auger Kits - Maxim




Transfer augers for external hoppers. Use 5-1/2' Auxiliary Auger Kit (p/n 2500007) as a replacement auger with the 48-Bushel Hopper Kit (this auger is included with the 48-Bushel Hopper Kits). The 6' Auxiliary Auger Kit (p/n 2500008) and 8' Auxiliary Auger Kit (p/n 2500009) will not work with the 48-Bushel Hopper.

2500008 Auxiliary Auger Kit, 6'
2500007 Auxiliary Auger Kit, 5-1/2'
2500009 Auxiliary Auger Kit, 8'
2000041 Replacement Gear Motor, Auxiliary Auger

Maxim Furnace Parts & Accessories


Bag Holder Kit - Maxim



Bag Holder attaches to the inside of the door of the 48-Bushel Hopper to support bag of fuel.

9804 Bag Holder Kit


Hopper Vibrator Kit - Maxim



Vibrator attaches to the side of the Maxim's integrated hopper to keep fuel from bridging. Template provided.

9691 Hopper Vibrator Kit

Auxiliary Auger Vibrator w/Timer Kit - Maxim



Vibrator is installed on the auxiliary auger connected to an external 43-bushel or 48-bushel hopper. For use with Auxiliary Auger Kits 2500007, 2500008 and 2500009 only. Vibration occurs based on timer setting.

9458 Auxiliary Auger Vibrator w/Timer Kit

Connectors, Lever Nut



For easy connections of wires, in three configurations (5-lever connector shown).


8200277 Electrical Connector, 2-Lever
 8200278 Electrical Connector, 3-Lever
 8200279 Electrical Connector, 5-Lever



Parts for all.

WoodMaster dealers carry complete lines of quality, affordable parts and accessories for most furnace brands, including new and existing heating systems, plus parts and accessories for HeatLink in-floor heat and complementary home comfort systems.

Our selection of hundreds of parts and accessories includes:



HEATLINK MANIFOLD



ASH GRATE SYSTEM



TACO PUMPS



ETC PANEL



WATER TO AIR HEAT EXCHANGER



THERMOPEX

Find your nearest dealer at WoodMaster.com

Your local WoodMaster dealer is: